

# TITAN 2 LED HYPER MULTI OPAL 1450MM (57.09 IN) 7100LM-8500LM-9700LM 850 IP66 DIMM 1-10V 48W-59W- 68W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	901461
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Rated power [W] - range:</b>	48/59/68
<b>Colour temperature [K]:</b>	5000
<b>Luminous flux of the luminaire [lm] - range:</b>	7100/8500/9700
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	RAL7035

## CHARACTERISTICS

Titan 2 LED Hyper Multi is a fitting from NEXT GEN line, which is a new generation of fittings in LED technology. The fitting, designed from scratch, allows new solutions improving the light distribution and temperature balance. Branded LED diodes and new LED modules have influence on a very high luminous efficacy. It guarantees the best required lighting level and energy saving up to 68%. The solution based on integration of the diffuser and LED module is applied in the fitting. The fitting has a lot of facilities making the mounting easier and faster: the system of diffuser suspension, adjustable mounting brackets ensuring the mounting tolerance +/-50mm. Standard equipment of the fitting: clips made of stainless steel (INOX). Motion sensor mounting height: up to 5 meters. The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of four settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.


# TITAN 2 LED HYPER MULTI OPAL 1450MM (57.09 IN) 7100LM-8500LM-9700LM 850 IP66 DIMM 1-10V 48W-59W-68W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	901461	<b>Dimensions (H/W/T/S) [mm]:</b>	1432/85/80
<b>EAN:</b>	5905963901461	<b>Dimensions [inches]:</b>	57.09
<b>Light source:</b>	LED module	<b>Mounting dimensions [mm]:</b>	970
<b>Rated power [W] - range:</b>	48/59/68	<b>Impact resistance:</b>	IK09
<b>Luminous flux of the luminaire [lm] - range:</b>	7100/8500/9700	<b>Ingress protection:</b>	IP66
<b>Supply voltage [V]:</b>	120-277	<b>Mounting version:</b>	surface, suspended
<b>Frequency [Hz]:</b>	50-60	<b>Working temperature [°C]:</b>	-20 +35 °C (-4 to 95 °F)
<b>Electrical protection class:</b>	I	<b>Number on the palette [pcs]:</b>	100
<b>Colour temperature [K]:</b>	5000	<b>Net weight [kg]:</b>	1.900
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Light distribution type:</b>	open space
<b>Beam angle [°]:</b>	120	<b>Flicker procent:</b>	30
<b>Diffuser material:</b>	PC	<b>Warranty [years]:</b>	5
<b>Diffuser type:</b>	OPAL	<b>UL certification:</b>	<a href="#">UL-US-2580505-3; UL-CA-2559005-3</a>
<b>Optics material:</b>	PC	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Material of the body:</b>	PC	<b>Plik LDT:</b>	<a href="#">Download</a>
<b>Colour of the body:</b>	RAL7035		

## LIGHT CURVES



# TITAN 2 LED HYPER MULTI OPAL 1450MM (57.09 IN) 7100LM-8500LM-9700LM 850 IP66 DIMM 1-10V 48W-59W- 68W

## TECHNICAL DETAILS

### DETAILED CARD



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich



tytan multi led

Card creation date: 12 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: