BARIS 40 LED Z 6175LM PLX I CL. IP44 1421MM 830 41W ANODE CO

DETAILED CARD



TECHNICAL PARAMETERS

Index:	131684
Rated power of the luminaire [W]*:	41
Luminous flux [lm]*:	6175
Colour temperature [K]:	3000
Ingress protection:	IP44
Energy efficiency class:	C
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

BARIS 40 LED Z 6175LM PLX I CL. IP44 1421MM 830 41W ANODE CO


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	131684
EAN:	5905963131684
Light source:	LED
Rated power of the luminaire [W]:	41
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	6175
Luminous efficacy [lm/W]:	151
Energy efficiency class:	C
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Diffuser material:	PC
Diffuser type:	OPAL
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	53/40/1421
Ingress protection:	IP44

Mounting version:	suspended
Net weight [kg]:	1.550
Category type:	luminaires and linear systems
LED lifespan L70B50 [h]:	150000
LED lifespan L80B10 [h]:	100000
LED lifespan L90B10 [h]:	50000
Supply voltage [V]:	220-240
Impact resistance:	IK06
Working temperature [°C]:	from 0 to +35
Warranty [years]:	5
CE certificate:	04/2026
ENEC Certificate:	PL BBJ/004/2022/M1/A1
Manual:	Download PDF
Environmental Product Declaration (EPD):	852/2025
Category of application:	office lighting
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018

LIGHT CURVES



Card creation date: 17 February 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 04/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl