

# DIONE LED PLUS EVO 2900LM 840 IP65 II CL. RCR OPAL WHITE 23W (H)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	192067
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	23
<b>Luminous flux [lm]*:</b>	2900
<b>Colour temperature [K]:</b>	4000
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Ring material:</b>	ABS

## CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy-saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows keeping the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency, and optimal use of electricity (Power Factor).

The fitting is offered in RCR version:

- sensor used to detect motion; for detection uses microwaves (active sensor).

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

# DIONE LED PLUS EVO 2900LM 840 IP65 II CL. RCR OPAL WHITE 23W (H)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	192067	Dimensions (H/W/T/S) [mm]:	ø340/115
EAN:	5905963192067	Mounting dimensions [mm]:	140
Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	23	Ingress protection:	IP65
Rated power of the luminaire [W]:	23	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50-60	Motion sensor:	yes
Luminous flux [lm]:	2900	Dimensions of single box [mm]:	340/340/116
Luminous efficacy [lm/W]:	126	Net weight [kg]:	1.180
Energy efficiency class:	E	Gross weight [kg]:	1.360
Electrical protection class:	II	Category type:	bulkheads
Colour temperature [K]:	4000	AC voltage range [V]:	220-240
Color rendering index (Ra) >:	80	LED lifespan L70B50 [h]:	118000
SDCM:	3	LED lifespan L80B10 [h]:	75000
Power factor:	0.95	LED lifespan L90B10 [h]:	36000
Beam angle [°]:	120	Light distribution type:	open space
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	OPAL	Warranty [years]:	5
Diffuser colour:	white	CE certificate:	<a href="#">12/2026</a>
Material of the body:	ABS	ENEC Certificate:	
Colour of the body:	white	Manual:	<a href="#">Download PDF</a>
Ring material:	ABS	Plik LDT:	<a href="#">Download</a>
Ring colour:	white		

# DIONE LED PLUS EVO 2900LM 840 IP65 II CL. RCR OPAL WHITE 23W (H)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white  
matt RAL 9003 painted vandal  
resistant (120DL118)

Card creation date: 25 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 12/2026