PROXIMA LED 3400LM 830 IP65 II CL. RCR OPAL WHITE (31W) (M)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	104169
Ingress protection:	IP65/54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	31
Luminous flux [lm]*:	3400
Colour temperature [K]:	3000
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface-mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA LED 3400LM 830 IP65 II CL. RCR OPAL WHITE (31W) (M)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	104169
EAN:	5905963104169
Light source:	LED module
Rated power of the luminaire [W]:	31
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	3400
Luminous efficacy [lm/W]:	110
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Power factor:	0.90
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	PP
Colour of the body:	white
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	ø390/110
Impact resistance:	IK10

Ingress protection:	IP65/54
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Motion sensor:	yes
Number on the palette [pcs]:	60
Net weight [kg]:	1.300
Category type:	bulkheads
Version:	RCR Merrytek
LED lifespan L70B50 [h]:	118000
LED lifespan L80B10 [h]:	75000
LED lifespan L90B10 [h]:	36000
SDCM:	3
Ring material:	ABS
Mounting dimensions [mm]:	165/165
Dimensions of single box [mm]:	100/390/390
AC voltage range [V]:	220-240
Warranty [years]:	5
CE certificate:	16/2026
Manual:	Download PDF
ISO Certificates:	9001:2015. 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

LIGHT CURVES



Card creation date: 19 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 16/2026

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl