

FACTOR LED XL C5-M 1M 56150LM 840 ASM DALI IP66 SH (400W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	489723
Ingress protection:	IP66
Rated power of the luminaire [W]*:	400
Luminous flux [lm]*:	55589
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	C
Warranty [years]:	5
Impact resistance:	IK09

CHARACTERISTICS

Very high-power floodlights used in the most demanding investments, professional sports facilities, football stadiums, where sporting events are broadcast by television in accordance with the highest standards. The prototype in the FACTOR family is the highly acclaimed FACTOR LED floodlight, consisting of 1-4 modules with a maximum luminous flux of approx. 150,000 lm. The new FACTOR XL series raises the bar by almost doubling the maximum luminous flux using only three modules and the highest luminous efficacy. All this is thanks to a compact and efficient design, which also translates into lower investment and operating costs for the facility. The exceptional quality of light is ensured by branded LEDs and professional optical systems. Excellent tightness and impact resistance parameters ensure operation in the most difficult weather conditions.

APPLICATION

Ports, quays, shipyards, drilling platforms and offshore infrastructure, chemical industry and refineries, bridges and infrastructure exposed to marine conditions, lighting on ships and ferries, industrial areas, sports fields, airports, car parks with high humidity and salinity. It can be used and works well both inside industrial, warehouse and sports halls, logistics centres, as well as outside – on sports fields, airports, car parks and manoeuvring areas. It can also illuminate building facades and external architectural elements.

FACTOR LED XL C5-M 1M 56150LM 840 ASM DALI IP66 SH (400W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	489723	LED lifespan L90B10 [h]:	540000
EAN:	5905963489723	Surge protection [kV]:	6
Light source:	LED module	Diffuser material:	szyba hartowana
Rated power of the luminaire [W]:	400	Diffuser type:	matrix led
Luminous flux [lm]:	55589	Material of the body:	aluminium
Supply voltage [V]:	220-240	Colour of the body:	RAL7016
Luminous efficacy [lm/W]:	140	Dimensions (H/W/T/S) [mm]:	368/624/227
Energy efficiency class:	C	Impact resistance:	IK09
Electrical protection class:	I	Mounting version:	top
Colour temperature [K]:	4000	Working temperature [°C]:	from -40 to +50
Color rendering index (Ra) >:	80	Dimensions of single box [mm]:	630/390/150
Mounting dimensions [mm]:	302/79	Net weight [kg]:	13.380
Ingress protection:	IP66	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
DIMM DALI:	yes	Warranty [years]:	5
Version:	1M	CE certificate:	76/2026
Light distribution type:	ASM	ENEC Certificate:	0404/ENEC/25
Corrosivity category:	C5-M	Environmental Product Declaration (EPD):	816/2025
Frequency [Hz]:	47-63	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
LED lifespan L70B50 [h]:	1840000	Manual:	Download PDF
LED lifespan L80B10 [h]:	1150000	Plik LDT:	Download

Card creation date: 28 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 76/2026