

LUMEDIC 595X595MM SM 7325LM RA95 4000K GLASS/PRM LNS IP65 I CL. W IK09 R 83W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---------------------|
| Index: | 789960 |
| Ingress protection: | IP65 |
| Impact resistance: | IK09 |
| Rated power of the luminaire [W]*: | 83 |
| Luminous flux [lm]*: | 7325 |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 95 |
| Energy efficiency class: | F |
| Electrical protection class: | I |
| Material of the body: | powder coated steel |

CHARACTERISTICS

Lumedic SM R is a specialist Cleanroom luminaire designed for clean rooms with increased hygiene and sterility requirements. Its design ensures ease of cleaning and high mechanical and environmental resistance. A robust steel housing with IP65 protection on the room side and IP50 on the technical side ensures complete tightness in a sterile environment, while allowing free air flow above the suspended ceiling. Service access is provided from the technical side (top inspection), allowing maintenance without interfering with the clean room.

The luminaire is characterised by very high colour rendering quality (CRI > 95), with high values for the R9 = 94.7 and R13 = 98.9 components. The R9 parameter, responsible for the reproduction of saturated red colours, is crucial in medical diagnostics, surgery and laboratory analyses, where precise differentiation of shades of blood, tissues and biological materials is critical. A high R9 value indicates the use of light sources with a full, continuous spectrum, which is not available for standard LED luminaires.

The R13 parameter refers to the faithful reproduction of skin tones and materials with light, pastel shades. An R13 value of 98.9 ensures a natural appearance of work surfaces, hands and staff faces, reducing eye strain and the risk of visual misjudgement in high-responsibility environments such as operating theatres, pharmaceutical laboratories and quality control rooms.

The front of the luminaire is made of aluminium and 4 mm thick tempered glass, resistant to impact (IK09 class) and chemicals. The modular shutter system (Glass / Opal / PRM) allows you to select the appropriate optical characteristics depending on the application requirements — from uniform, diffused light to precise directional distribution. The SM R version is designed for installation in modular ceilings.

APPLICATION

- laboratories (microbiological, pharmaceutical, chemical),
- hospitals (operating theatres, intensive care units, diagnostic laboratories),
- food and pharmaceutical industry,
- cleanrooms in electronics and semiconductor manufacturing.

LUMEDIC 595X595MM SM 7325LM RA95 4000K GLASS/PRM LNS IP65 I CL. W IK09 R 83W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------------|---|---|
| Index: | 789960 | Dimensions (H/W/T/S) [mm]: | 595/595/65 |
| EAN: | 5905963789960 | Mounting dimensions [mm]: | 600/600 |
| Light source: | LED module | Impact resistance: | IK09 |
| Rated power of the luminaire [W]: | 83 | Ingress protection: | IP65 |
| Supply voltage [V]: | 220 - 240 | Mounting version: | recessed |
| Frequency [Hz]: | 0/50/60 | Working temperature [°C]: | from -20 to +35 |
| Luminous flux [lm]: | 7325 | LED lifespan L70B50 [h]: | 200000 |
| Luminous efficacy [lm/W]: | 88 | LED lifespan L80B10 [h]: | 100000 |
| Energy efficiency class: | F | LED lifespan L90B10 [h]: | 50000 |
| Electrical protection class: | I | Number on the palette [pcs]: | 16 |
| Colour temperature [K]: | 4000 | Net weight [kg]: | 11 |
| Color rendering index (Ra) >: | 95 | Photobiological safety: | RG0 - exempt (no photobiological hazard) |
| Power factor: | 0.95 | Warranty [years]: | 5 |
| Diffuser material: | szyba hartowana | CE certificate: | 37/2026 |
| Diffuser type: | Glass/PRM | ENEC Certificate: | 0463/ENEC/25 |
| Optics material: | PS | PZH certificate: | B-BK-60112-0109/2026 |
| Optics: | PRM | Environmental Product Declaration (EPD): | 869/2025 |
| Material of the body: | powder coated steel | Manual: | Download PDF |
| Colour of the body: | biały Ral 9003 | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018, ISO 3 - 9 (ISO 14644-1:2015) |
| Ring material: | aluminium | Plik LDT: | Download |
| Ring colour: | biały Ral 9003 | | |

Card creation date: 24 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 37/2026