

CAMEA SMD LED 16W MAT BIAŁY 3000K LC

DETAILED CARD



TECHNICAL PARAMETERS

Index:	067273
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	16
Luminous flux [lm]*:	2000
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	PP
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, ingress protection class IP44 and an integrated energy-saving lights source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

CAMEA SMD LED 16W MAT BIAŁY 3000K LC

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	16	Dimensions (H/W/T/S) [mm]:	ø300/90
Light source:	LED module	Impact resistance:	IK10
Colour temperature [K]:	3000	Ingress protection:	IP44
Luminous flux [lm]:	2000	Mounting version:	surface
Rated power of the luminaire [W]:	19	Working temperature [°C]:	from -17 to +35
Diffuser type:	OPAL	Net weight [kg]:	0.600
Supply voltage [V]:	220-240	CE certificate:	397/2023
Frequency [Hz]:	50 - 60	Index:	067273
Energy efficiency class:	E	EAN:	5905963067273
Luminous efficacy [lm/W]:	105	Category type:	bulkheads
Electrical protection class:	I	Luminaire rated power 0min [W]:	22
Colour rendering index:	>80	ETIM class:	EC002892
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.95	Warranty [years]:	5
Material of the body:	PP	LED lifespan L80B20 [h]:	60000
Ring colour:	white	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES

