

CAMEA SMD LED RCR 12W MAT BIAŁY 4000K LC

DETAILED CARD



TECHNICAL PARAMETERS

Index:	066900
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	12
Luminous flux [lm]*:	1400
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	PP
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, ingress protection class IP44 and an integrated energy-saving lights source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

CAMEA SMD LED RCR 12W MAT BIAŁY 4000K LC

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	12	Dimensions (H/W/T/S) [mm]:	ø300/90
Light source:	LED module	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP44
Luminous flux [lm]:	1400	Mounting version:	surface
Rated power of the luminaire [W]:	13	Working temperature [°C]:	from -17 to +35
Diffuser type:	OPAL	Net weight [kg]:	0.670
Supply voltage [V]:	220-240	CE certificate:	397/2023
Frequency [Hz]:	50 - 60	Index:	066900
Motion sensor:	1	EAN:	5905963066900
Energy efficiency class:	E	Category type:	bulkheads
Luminous efficacy [lm/W]:	107	Luminaire rated power O_{min} [W]:	14
Electrical protection class:	I	ETIM class:	EC002892
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.95	LED lifespan L80B20 [h]:	60000
Material of the body:	PP	Manual:	Download PDF
Ring colour:	white	Plik LDT:	Pobierz

Card creation date: 27 October 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 397/2023