

# CAMEA SMD LED RCR 9W MAT BIAŁY 3000K LC

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	067280
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	9
Luminous flux [lm]*:	920
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	PP
Diffuser type:	OPAL

## CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, ingress protection class IP44 and an integrated energy-saving lights source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10).

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

# CAMEA SMD LED RCR 9W MAT BIAŁY 3000K LC

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	9	Dimensions (H/W/T/S) [mm]:	ø300/90
Light source:	LED module	Impact resistance:	IK10
Colour temperature [K]:	3000	Ingress protection:	IP44
Luminous flux [lm]:	920	Mounting version:	surface
Rated power of the luminaire [W]:	10	Working temperature [°C]:	from -17 to +35
Diffuser type:	OPAL	Net weight [kg]:	0.600
Supply voltage [V]:	220-240	CE certificate:	<a href="#">397/2023</a>
Frequency [Hz]:	50 - 60	Index:	067280
Motion sensor:	yes	EAN:	5905963067280
Energy efficiency class:	F	Category type:	bulkheads
Luminous efficacy [lm/W]:	92	Luminaire rated power $P_{min}$ [W]:	10
Electrical protection class:	I	ETIM class:	EC002892
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.95	LED lifespan L80B20 [h]:	60000
Material of the body:	PP	Manual:	<a href="#">Download PDF</a>
Ring colour:	white	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES

