

CAMEA SMD LED RCR 9W MAT BIAŁY 4000K LC

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 066924 |
| Ingress protection: | IP44 |
| Impact resistance: | IK10 |
| Nominal power [W]: | 9 |
| Luminous flux [lm]*: | 980 |
| Colour temperature [K]: | 4000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | E |
| Material of the body: | PP |
| Diffuser type: | OPAL |

CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, ingress protection class IP44 and an integrated energy-saving lights source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for indoor use (usable rooms, staircases, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

CAMEA SMD LED RCR 9W MAT BIAŁY 4000K LC

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Nominal power [W]: | 9 | Dimensions (H/W/T/S) [mm]: | ø300/90 |
| Light source: | LED module | Impact resistance: | IK10 |
| Colour temperature [K]: | 4000 | Ingress protection: | IP44 |
| Luminous flux [lm]: | 980 | Mounting version: | surface |
| Rated power of the luminaire [W]: | 10 | Working temperature [°C]: | from -17 to +35 |
| Diffuser type: | OPAL | Net weight [kg]: | 0.600 |
| Supply voltage [V]: | 220-240 | CE certificate: | 397/2023 |
| Frequency [Hz]: | 50 - 60 | Index: | 066924 |
| Motion sensor: | yes | EAN: | 5905963066924 |
| Energy efficiency class: | E | Category type: | bulkheads |
| Luminous efficacy [lm/W]: | 98 | Luminaire rated power O_{min} [W]: | 10 |
| Electrical protection class: | I | ETIM class: | EC002892 |
| Colour rendering index: | >80 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| SDCM: | ≤ 3 | Warranty [years]: | 5 |
| Power factor: | 0.95 | LED lifespan L80B20 [h]: | 60000 |
| Material of the body: | PP | Manual: | Download PDF |
| Ring colour: | white | Plik LDT: | |

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 397/2023