

EXPO MODULAR ZOOM SURFACE 3950LM DALI 37-57D BLACK MATT TEXTURE 935 35W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	231698
Ingress protection:	IP20
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	3950
Colour temperature [K]:	3500
Color rendering index (Ra) >:	90
Material of the body:	aluminium
Colour of the body:	black matt texture
Optics material:	PMMA
Optics:	lens

CHARACTERISTICS

Expo Modular ZOOM — lighting that flexibly adapts to changing spaces. ZOOM is a solution for places that often evolve — boutique spaces, concept stores, seasonal exhibitions, tasting and premium product galleries, product showrooms, and office spaces. The advanced lens allows for smooth adjustment of the beam angle in the ranges of 22–32° and 37–57°, which makes it possible to use the luminaire both as an accent and as display and fill lighting. Thanks to ZOOM, the light ‘follows’ the arrangement — no need to replace the luminaires, just fine-tune them. It allows you to maintain architectural consistency even with very frequent changes in the display. The ZOOM 37–57° TIR zoom offers selective light with variable distribution, allowing for a smooth change in angle from medium to wide while maintaining uniform beam characteristics. It enables dynamic lighting adjustment, acting as a fill light that responds flexibly to the layout and allows you to create multiple display scenes from a single spotlight, while maintaining the visual consistency of the space. It is particularly useful in showrooms, seasonal spaces and displays of varying scale and layout, as well as in boutiques, offices, exhibitions and museums.

APPLICATION

Expo Modular ZOOM is a solution designed for spaces that require maximum flexibility and frequent rearrangements. The system allows for precise adjustment of lighting to the current needs of the exhibition, making it ideal for boutiques, concept stores, showrooms, seasonal spaces, tasting areas, premium product galleries, showrooms and modern offices.

EXPO MODULAR ZOOM SURFACE 3950LM DALI 37-57D BLACK MATT TEXTURE 935 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	231698	Mounting dimensions [mm]:	50(2xø5)
EAN:	5905963231698	Ingress protection:	IP20
Light source:	COB	Mounting version:	surface
Rated power of the luminaire [W]:	35	Tilt angle adjustment [°]:	yes
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	0/50/60	Dimensions of single box [mm]:	245
Luminous flux [lm]:	3950	Number on the palette [pcs]:	270
Luminous efficacy [lm/W]:	113	Net weight [kg]:	1.170
Energy efficiency class:	E	Gross weight [kg]:	1.280
Electrical protection class:	II	Category type:	spotlight
Colour temperature [K]:	3500	LED lifespan L70B50 [h]:	50000
Color rendering index (Ra) >:	90	LED lifespan L80B10 [h]:	100000
Beam angle [°]:	37-57	Warranty [years]:	5
Optics material:	PMMA	CE certificate:	156/2025
Optics:	lens	Manual:	Download PDF
Material of the body:	aluminium	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	black matt texture	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	235.4/202/ø82		

Card creation date: 02 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 156/2025