# EXPO MODULAR ZOOM SURFACE 3950LM 22-32D WHITE MATT TEXTURE 940 35W

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 231773 |
| **Ingress protection:** | IP20 |
| **Rated power of the luminaire [W]*:** | 35 |
| **Luminous flux [lm]*:** | 3950 |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 90 |
| **Material of the body:** | aluminium |
| **Colour of the body:** | white matt texture |
| **Optics material:** | PMMA |
| **Optics:** | lens |

## CHARACTERISTICS

**Expo Modular ZOOM — lighting that flexibly adapts to changing spaces.**ZOOM is a solution for places that often evolve — boutique spaces, concept stores, seasonal exhibitions, tasting and premium product galleries, product showrooms, and office spaces. The advanced lens allows for smooth adjustment of the beam angle in the ranges of 22–32° and 37–57°, which makes it possible to use the luminaire both as an accent and as display and fill lighting. Thanks to ZOOM, the light ‘follows’ the arrangement — no need to replace the luminaires, just fine-tune them. It allows you to maintain architectural consistency even with very frequent changes in the display. ZOOM 22–32° TIR zoom provides focused light with variable distribution, allowing smooth adjustment of the angle from narrow to medium wide while maintaining the same beam characteristics. It allows for dynamic lighting adjustment, so that accent lighting can follow the changing arrangement, creating multiple display scenes from a single spotlight while maintaining the visual consistency of the space. This solution is ideal for showrooms, seasonal spaces and exhibitions with variable scale and layout, as well as boutiques, offices, exhibitions and museums.

## APPLICATION

Expo Modular ZOOM is a solution designed for spaces that require maximum flexibility and frequent rearrangements. The system allows for precise adjustment of lighting to the current needs of the exhibition, making it ideal for boutiques, concept stores, showrooms, seasonal spaces, tasting areas, premium product galleries, showrooms and modern offices.

# EXPO MODULAR ZOOM SURFACE 3950LM 22-32D WHITE MATT TEXTURE 940 35W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 231773 |
| **EAN:** | 5905963231773 |
| **Light source:** | COB |
| **Rated power of the luminaire [W]:** | 35 |
| **Supply voltage [V]:** | 220-240 |
| **Frequency [Hz]:** | 0/50/60 |
| **Luminous flux [lm]:** | 3950 |
| **Luminous efficacy [lm/W]:** | 113 |
| **Energy efficiency class:** | E |
| **Electrical protection class:** | II |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 90 |
| **SDCM:** | 3 |
| **Beam angle [°]:** | 22-32 |
| **Optics material:** | PMMA |
| **Optics:** | lens |
| **Material of the body:** | aluminium |
| **Colour of the body:** | white matt texture |
| **Dimensions (H/W/T/S) [mm]:** | 235.4/202/ø82 |

| | |
|---|---|
| **Mounting dimensions [mm]:** | 50(2xø5) |
| **Ingress protection:** | IP20 |
| **Mounting version:** | surface |
| **Tilt angle adjustment [°]:** | yes |
| **Dimensions of single box [mm]:** | 245 |
| **Number on the palette [pcs]:** | 270 |
| **Net weight [kg]:** | 1.170 |
| **Gross weight [kg]:** | 1.280 |
| **Category type:** | spotlight |
| **LED lifespan L70B50 [h]:** | 50000 |
| **LED lifespan L80B10 [h]:** | 100000 |
| **Power factor:** | 0.98 |
| **Working temperature [°C]:** | from 0 to +35 |
| **Photobiological safety:** | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| **Warranty [years]:** | 5 |
| **CE certificate:** | 156/2025 |
| **Manual:** | Download PDF |
| **ISO Certificates:** | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| **Plik LDT:** | Download |

Card creation date: 02 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 156/2025

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl