

EXPO MODULAR SURFACE 4100LM 38D BLACK MATT TEXTURE 927 35W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	236921
Ingress protection:	IP20
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	4100
Colour temperature [K]:	2700
Color rendering index (Ra) >:	90
Material of the body:	aluminium
Colour of the body:	black matt texture
Optics:	reflector
Beam angle [°]:	38

CHARACTERISTICS

Expo Modular — a tool for creating a carefully considered lighting design. EXPO Modular is a projector luminaire developed from the ground up, offering users a range of new functionalities. Low UGR glare effect, precise optics, high CRI, the possibility of expanding the luminaire's functionality or giving it an individual character through a wide range of accessories such as ecoPET screens or accessories such as unusual shades, screens and covers made with 3D printing. The luminaire's design ensures optimal thermal performance and allows for changing the lighting angles, as well as customising the colour of the ring and body. EXPO Modular is a high-quality aluminium projector with a COB LED light source. Versatile application with a track system. No ultraviolet or infrared radiation, high colour rendering index, high luminous efficacy and long service life. 38° mirror reflector — balanced, natural display light. The 38° version provides a soft, even light spot with a gentle edge and soft transition, making it ideal for offices to highlight visual communication elements, as well as boutiques or elegant delicatessens, where visual comfort is as important as the legibility of the display. It is a light that 'breathes' with the space, creating an eye-friendly light distribution — it emphasises materials and their texture without excessive contrast, creates natural product modelling and allows you to build light-perceived interiors that are a balance between the sharpness of narrow beams and the soft filling of wide beams, while ensuring sufficiently good face modulation.

APPLICATION

The light from the 38° mirror reflector creates a balanced, natural, and harmonious illumination that seamlessly integrates with the surroundings. Its even luminance distribution and smooth beam edge make it ideal for spaces requiring high-quality visual perception. This lighting subtly highlights materials, textures, and colors, ensuring natural product shaping without excessive contrast or over-dramatizing the display. This light pattern perfectly suits the needs of offices, where it supports the clarity of visual communication, as well as boutiques and elegant delicatessens, where visual comfort is as important as the attractiveness of the displayed goods. It is also used in exhibitions, museums, and markets, providing a base layer of light for medium-scale displays, and anywhere where a natural perception of space and products is important.

EXPO MODULAR SURFACE 4100LM 38D BLACK MATT TEXTURE 927 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	236921	Colour of the body:	black matt texture
EAN:	5905963236921	Dimensions (H/W/T/S) [mm]:	241.9/202/ø82
Light source:	COB	Mounting dimensions [mm]:	50(2xø5)
Rated power of the luminaire [W]:	35	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	0/50/60	Dimensions of single box [mm]:	245/230/90
Luminous flux [lm]:	4100	Number on the palette [pcs]:	270
Luminous efficacy [lm/W]:	117	Net weight [kg]:	1.145
Energy efficiency class:	D	Gross weight [kg]:	1.255
Electrical protection class:	II	LED lifespan L70B50 [h]:	50000
Colour temperature [K]:	2700	LED lifespan L80B10 [h]:	100000
Color rendering index (Ra) >:	90	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	3	Warranty [years]:	5
Power factor:	0.98	CE certificate:	156/2025
Beam angle [°]:	38	Manual:	Download PDF
Optics material:	aluminium	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Optics:	reflector	Plik LDT:	Download
Material of the body:	aluminium		

Card creation date: 13 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 156/2025