EXPO MODULAR HR SURFACE 3250LM 18D WHITE MATT TEXTURE 935 35W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	263705
Ingress protection:	IP20
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	3250
Colour temperature [K]:	3500
Color rendering index (Ra) >:	90
Electrical protection class:	II
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	white matt texture

CHARACTERISTICS

Expo Modular HR — selective light with full control over perception. The HR version uses a deeply embedded COB diode and a precise mirror reflector to create light of exceptional purity and minimal glare. It is a solution for spaces where light should be subtle but extremely precise — emphasising the structure, colour and quality of products with minimal illumination of the surroundings. HR 18° Mirror is a selective light of the highest purity, which provides a perfectly defined beam edge, minimal glare and exceptional clarity and precision. It creates a highly selective spatial effect, faithfully reproduces colour and perfectly emphasises texture and material. It is ideal for presenting luxury products, architectural details and displays that require maximum attention. It is suitable for boutiques, offices, exhibitions and museums.

APPLICATION

HR is ideal for exhibitions where objects need to be strongly distinguished from the background, offices where visual communication elements or architectural accents need to be strongly emphasised. It is used in boutiques, jewellery shops, arts and crafts shops to highlight the most important products, and in delicatessens offering premium products: artisan cheeses, spirits, gourmet products that require special emphasis in the offer, especially in combination with specialised light spectra. The light spot is clear, stable, with a strong and short light transition—exactly what is expected in accent lighting designs while maintaining a soft edge to the light spot. The available angles of 18° and 37° allow you to create both very narrow accents and more universal light. HR is a luminaire for building precision and clear visual narrative—without unnecessary compromises. The optics are available in a full range of light colours.

EXPO MODULAR HR SURFACE 3250LM 18D WHITE MATT TEXTURE 935 35W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	263705
EAN:	5905963263705
Light source:	COB
Rated power of the luminaire [W]:	35
Supply voltage [V]:	220-240
Frequency [Hz]:	0/50/60
Luminous flux [lm]:	3250
Luminous efficacy [lm/W]:	93
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	3500
Color rendering index (Ra) >:	90
SDCM:	3
Beam angle [°]:	18
LED lifespan L70B50 [h]:	50000
LED lifespan L80B10 [h]:	100000
Power factor:	0.98
Working temperature [°C]:	from 0 to +35
Optics material:	aluminium

Optics:	reflector
Material of the body:	aluminium
Colour of the body:	white matt texture
Dimensions (H/W/T/S) [mm]:	267.9/202/ø82
Mounting dimensions [mm]:	50(2xø5)
Ingress protection:	IP20
Mounting version:	surface
Dimensions of single box [mm]:	245/230/90
Number on the palette [pcs]:	270
Net weight [kg]:	1.200
Gross weight [kg]:	1.310
Category type:	spotlight
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	156/2025
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

Card creation date: 16 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 156/2025

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl