

EXPO MODULAR GOLD TRACK 1900LM 38D BLACK MATT TEXTURE 28W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|--------------------|
| Index: | 251702 |
| Ingress protection: | IP20 |
| Rated power of the luminaire [W]*: | 28 |
| Luminous flux [lm]*: | 1900 |
| Colour temperature [K]: | 2700 |
| Color rendering index (Ra) >: | 80 |
| Material of the body: | aluminium |
| Colour of the body: | black matt texture |
| Optics: | reflector |
| Beam angle [°]: | 38 |

CHARACTERISTICS

Expo Modular — a tool for creating a carefully considered lighting design. EXPO Modular is a projector luminaire developed from the ground up, offering users a range of new functionalities. Low UGR glare effect, precise optics, high CRI, the possibility of expanding the luminaire's functionality or giving it an individual character through a wide range of accessories such as ecoPET screens or accessories such as unusual shades, screens and covers made with 3D printing. The luminaire's design ensures optimal thermal performance and allows for changing the lighting angles, as well as customising the colour of the ring and body. EXPO Modular is a high-quality aluminium projector with a COB LED light source. Versatile application with a track system. No ultraviolet or infrared radiation, high colour rendering index, high luminous efficacy and long service life. 38° mirror reflector — balanced, natural display light. The 38° version provides a soft, even light spot with a gentle edge and soft transition, making it ideal for offices to highlight visual communication elements, as well as boutiques or elegant delicatessens, where visual comfort is as important as the legibility of the display. It is a light that 'breathes' with the space, creating an eye-friendly light distribution — it emphasises materials and their texture without excessive contrast, creates natural product modelling and allows you to build light-perceived interiors that are a balance between the sharpness of narrow beams and the soft filling of wide beams, while ensuring sufficiently good face modulation.

APPLICATION

The light from the 38° mirror reflector creates a balanced, natural, and harmonious illumination that softly integrates with the surroundings. Thanks to its even luminance distribution and soft beam edge, it is ideal for spaces requiring high-quality visual perception. This lighting subtly highlights materials, textures, and colors, ensuring natural product shaping without excessive contrast or overly dramatic displays. This light pattern perfectly suits the needs of offices, where it supports the clarity of visual communication, as well as boutiques and elegant delicatessens, where visual comfort is as important as the attractiveness of the displayed goods. It is also used in exhibitions, museums, and markets, providing a base layer of light for medium-scale displays, and anywhere where a natural perception of space and products is important. GOLD Effect: Warm, sunny light with an amber hue. Application: Relaxation and wellness areas where you want to bathe in warm, sunny light. Perfect for highlighting gold jewelry displays. Perfect as a lighting addition to interiors with brass details and very warm wood. It works well in patisseries and for illuminating baked goods, highlighting the warm colors of flowers.

EXPO MODULAR GOLD TRACK 1900LM 38D BLACK MATT TEXTURE 28W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|---------------------------------------|---|
| Index: | 251702 | Colour of the body: | black matt texture |
| EAN: | 5905963251702 | Dimensions (H/W/T/S) [mm]: | 257.9/167/ø84 |
| Light source: | COB | Ingress protection: | IP20 |
| Rated power of the luminaire [W]: | 28 | Mounting version: | track |
| Supply voltage [V]: | 220-240 | Dimensions of single box [mm]: | 245 |
| Frequency [Hz]: | 0/50/60 | Number on the palette [pcs]: | 270 |
| Luminous flux [lm]: | 1900 | Net weight [kg]: | 0.915 |
| Luminous efficacy [lm/W]: | 68 | Gross weight [kg]: | 1.025 |
| Energy efficiency class: | G | Version: | GOLD |
| Electrical protection class: | II | LED lifespan L70B50 [h]: | 50000 |
| Colour temperature [K]: | 2700 | LED lifespan L80B10 [h]: | 100000 |
| Color rendering index (Ra) >: | 80 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| SDCM: | 3 | Warranty [years]: | 5 |
| Power factor: | 0.98 | CE certificate: | 156/2025 |
| Beam angle [°]: | 38 | Manual: | Download PDF |
| Optics material: | aluminium | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| Optics: | reflector | Plik LDT: | Download |
| Material of the body: | aluminium | | |

Card creation date: 13 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 156/2025