

# BARIS 52 LED P GK CONNECTOR L 2400LM 840 IP20 I CL. DALI PLX ANODE CO 18W

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |        |
|------------------------------------|--------|
| Index:                             | 268687 |
| Rated power of the luminaire [W]*: | 18     |
| Energy efficiency class:           | D      |
| Colour temperature [K]:            | 4000   |
| Diffuser type:                     | OPAL   |

## CHARACTERISTICS

The key feature of L, T, X connectors is that they are equipped with integrated electronics and a diffuser, thanks to which the profile route bends remain illuminated along the entire length. Body is made of anodized aluminium profile in grey or aluminium profile painted white or black (other colors available on request). The optical system is complemented by a dedicated, flexible opal cover that evenly illuminates the connector. There is no division into surface mounted and suspended versions, which make the solution more universal.

Connectors (T, X, L) are supplied with an OPAL diffuser.

Connectors T, X, L UGR, and PRM diffusers are available on request.

## APPLICATION

BARIS 52 LED connectors in the shape of the letter L, T, X and straight connectors create extraordinary opportunities to configure the light line matched to the character and shape of the room, allowing you to create virtually unlimited straight sequences, figures and patterns.


# BARIS 52 LED P GK CONNECTOR L 2400LM 840 IP20 I CL. DALI PLX ANODE CO 18W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                                          |                                               |
|-----------------------------------|---------------|------------------------------------------|-----------------------------------------------|
| Index:                            | 268687        | Colour of the body:                      | grey                                          |
| EAN:                              | 5905963268687 | Dimensions (H/W/T/S) [mm]:               | 610/610/52                                    |
| Rated power of the luminaire [W]: | 18            | Category of application:                 | office lighting                               |
| Luminous flux [lm]:               | 2400          | DIMM DALI:                               | yes                                           |
| Luminous efficacy [lm/W]:         | 133           | Warranty [years]:                        | 5                                             |
| Energy efficiency class:          | D             | CE certificate:                          | <a href="#">42/2026</a>                       |
| Colour temperature [K]:           | 4000          | Manual:                                  | <a href="#">Download PDF</a>                  |
| LED lifespan L70B50 [h]:          | 150000        | Environmental Product Declaration (EPD): | <a href="#">852/2025</a>                      |
| LED lifespan L80B10 [h]:          | 100000        | Version:                                 | L connector                                   |
| LED lifespan L90B10 [h]:          | 50000         | ISO Certificates:                        | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| Diffuser type:                    | OPAL          |                                          |                                               |

## LIGHT CURVES



Card creation date: 19 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 42/2026

 **LENA**  
LIGHTING

Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)