

LUMEDIC 595X595MM SM 11125LM RA80 3000K GLASS/OPAL IP65 I CL. W IK09 83W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	505584
Ingress protection:	IP65
Impact resistance:	IK09
Luminous flux [lm]*:	11125
Color rendering index (Ra) >:	80
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	szyba hartowana
Diffuser type:	Glass/Opal
Mounting version:	recessed

CHARACTERISTICS

Lumedic SM this is a specialist cleanroom luminaire designed for cleanrooms with an air cleanliness class of ISO 3–9, in accordance with ISO 14644-1:2015 Cleanroom, and meeting stringent hygiene and sterility requirements. The design ensures ease of cleaning and high mechanical and environmental resistance. A robust steel housing with an IP65 rating on both the room side and the technical space side ensures complete airtightness in a sterile environment, whilst allowing free airflow above the suspended ceiling.

The luminaire front is made of aluminium and 4 mm thick tempered glass, resistant to impact (IK09 class) and chemical agents. The modular diffuser system (Glass / Opal / PRM) allows for the selection of the appropriate optical characteristics depending on the application requirements — from uniform, diffused light to precise directional light distribution. The SM version is designed for installation in modular ceilings.

APPLICATION

Application

- laboratories (microbiological, pharmaceutical, chemical),
- hospitals (operating theatres, intensive care units, diagnostic laboratories),
- food and pharmaceutical industry,
- cleanrooms in electronics and semiconductor manufacturing.

LUMEDIC 595X595MM SM 11125LM RA80 3000K GLASS/OPAL IP65 I CL. W IK09 83W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	505584	Ring colour:	biały Ral 9003
EAN:	5905963505584	Dimensions (H/W/T/S) [mm]:	595/595/65
Light source:	LED module	Mounting dimensions [mm]:	600/600
Rated power of the luminaire [W]:	83	Impact resistance:	IK09
Supply voltage [V]:	220 - 240	Ingress protection:	IP65
Frequency [Hz]:	0/50/60	Mounting version:	recessed
Luminous flux [lm]:	11125	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	134	Number on the palette [pcs]:	16
Energy efficiency class:	E	Net weight [kg]:	7.600
Electrical protection class:	I	Gross weight [kg]:	8.200
Colour temperature [K]:	3000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Color rendering index (Ra) >:	80	Warranty [years]:	5
Power factor:	0.95	CE certificate:	55/2026
Diffuser material:	szyba hartowana	ENEC Certificate:	0463/ENEC/25
Diffuser type:	Glass/Opal	Environmental Product Declaration (EPD):	869/2025
Optics material:	PS	Manual:	Download PDF
Optics:	OPAL	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018, ISO 3 - 9 (ISO 14644-1:2015)
Material of the body:	powder coated steel	PZH certificate:	B-BK-60112-0109/2026
Colour of the body:	biały Ral 9003	Plik LDT:	Download
Ring material:	aluminium		

Card creation date: 28 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 55/2026