TERRACO IN LED 400LM IP65 I CL. 840 8W WHITE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	995972
Rated power of the luminaire [W]*:	8
Luminous flux [lm]*:	400
Colour temperature [K]:	4000
Ingress protection:	IP65
Color rendering index (Ra) >:	80
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Dimensions (H/W/T/S) [mm]:	130/180/103

CHARACTERISTICS

The Terraco IN is an architectural luminaire with a modern construction, distinguished by its striking minimalist design. The body is made of weather-resistant, powder-coated aluminium. It is designed for illuminating building façades. It features a high IP65 protection rating and IK08 impact resistance. It is designed for flush-mounted installation. The set includes a mounting box.

APPLICATION

The Terraco IN luminaire is ideal for external lighting of building façades, terraces, balconies and walkways. It can also be successfully used indoors, where it emphasises the modern character of the space. It is the perfect solution for striking illumination of contemporary architecture.

TERRACO IN LED 400LM IP65 I CL. 840 8W WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	995972
EAN:	5905963995972
Light source:	LED module
Rated power of the luminaire [W]:	8
Supply voltage [V]:	220-240
AC voltage range [V]:	176-264
Frequency [Hz]:	50/60
Luminous flux [lm]:	400
Luminous efficacy [lm/W]:	50
Energy efficiency class:	G
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
LED lifespan L70B50 [h]:	127000
LED lifespan L80B10 [h]:	80000
LED lifespan L90B10 [h]:	38000

Diffuser material:	PC
Diffuser colour:	transparent
Material of the body:	aluminium
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	130/180/103
Mounting dimensions [mm]:	123/70
Ingress protection:	IP65
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	168
Net weight [kg]:	1.200
Category type:	accent lighting
Warranty [years]:	5
CE certificate:	65/2026
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 29 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 65/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl