SPARK PRO LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	607639
Ingress protection:	IP44
Luminous flux of the luminaire [lm] - range:	250 - 980
Supply voltage [V]:	3.7
Electrical protection class:	III
Color rendering index (Ra) >:	80
Charging time [h:min]:	3
Battery life [h:min]:	1.40-11
Battery:	Li-Ion 3,7V
Dimensions (H/W/T/S) [mm]:	180/70/40

CHARACTERISTICS

This work light is the perfect solution for mechanics, tradespeople and DIY enthusiasts. It is a modern work light that allows you to direct the beam in various directions (thanks to its swivel head). The lamp is designed to illuminate the work area. It is particularly useful in garages servicing cars, vans and lorries. The replaceable battery can be charged separately (away from the lamp) using a C-type connector.

APPLICATION

Car repair shops (repairs for cars, vans and lorries), car detailing centres, car washes, mobile repair services, etc.

SPARK PRO LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	607639
EAN:	5905963607639
Light source:	LED
Luminous flux of the luminaire [lm] - range:	250 - 980
Supply voltage [V]:	3.7
Electrical protection class:	III
Color rendering index (Ra) >:	80
Charging time [h:min]:	3
Battery life [h:min]:	1.40-11
Battery:	Li-Ion 3,7V
Battery capacity [mAh]:	2600

Diffuser type:	transparent
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	180/70/40
Ingress protection:	IP44
Working temperature [°C]:	from -20 to +35
Switch:	yes
Magnet:	yes
Net weight [kg]:	0.520
Accessories included:	1 x 2600mAh 3.7V Li-Ion battery with a Type-C charging port – the battery can be charged separately from the lamp
CE certificate:	67/2026
Manual:	Download PDF

SPARK PRO LED

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
607660	External charger for Li-ion batteries: 3.7V / 2600 mAh (SPARK LED lamp range)
607677	Replaceable Li-ion battery: 3.7V / 2600 mAh (SPARK LED lamp range)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 67/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl