CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	978883
Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	35
Luminous flux of the luminaire [lm] - range:	4450
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt

CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	978883
EAN:	5905963978883
Light source:	LED
Rated power [W] - range:	35
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux of the luminaire [lm] - range:	4450
Luminous efficacy [lm/W]:	127
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Beam angle [°]:	114
Surge protection [kV]:	2
Diffuser material:	PS
Diffuser type:	matt
Diffuser colour:	milky
Optics material:	PMMA
Material of the body:	coated aluminium


Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	400/400/39
Impact resistance:	IK07
Ingress protection:	IP40
Mounting version:	surface
Working temperature [°C]:	from 0 to +35
DIMM DALI:	yes
Number on the palette [pcs]:	44
Net weight [kg]:	0.900
LED lifespan L70B50 [h]:	50000
LED lifespan L80B10 [h]:	100000
Light distribution type:	lambertian
Warranty [years]:	5
CE certificate:	69/2026
Environmental Product Declaration (EPD):	869/2025
Manual:	Download PDF
ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Plik LDT:	Download

CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
413995	CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish



CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish (413995)

Card creation date: 09 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 69/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl