

# CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	978883
<b>Ingress protection:</b>	IP40
<b>Impact resistance:</b>	IK07
<b>Rated power [W] - range:</b>	35
<b>Luminous flux of the luminaire [lm] - range:</b>	4450
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	coated aluminium
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	matt

## CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

## APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

# CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	978883	<b>Material of the body:</b>	coated aluminium
<b>EAN:</b>	5905963978883	<b>Colour of the body:</b>	black
<b>Light source:</b>	LED	<b>Dimensions (H/W/T/S) [mm]:</b>	400/400/39
<b>Rated power [W] - range:</b>	35	<b>Impact resistance:</b>	IK07
<b>Supply voltage [V]:</b>	220-240	<b>Ingress protection:</b>	IP40
<b>Frequency [Hz]:</b>	50-60	<b>Mounting version:</b>	surface
<b>Luminous flux of the luminaire [lm] - range:</b>	4450	<b>Working temperature [°C]:</b>	from 0 to +35
<b>Luminous efficacy [lm/W]:</b>	127	<b>DIMM DALI:</b>	yes
<b>Energy efficiency class:</b>	D	<b>Number on the palette [pcs]:</b>	44
<b>Electrical protection class:</b>	II	<b>Net weight [kg]:</b>	0.900
<b>Colour temperature [K]:</b>	4000	<b>LED lifespan L70B50 [h]:</b>	50000
<b>Color rendering index (Ra) &gt;:</b>	80	<b>LED lifespan L80B10 [h]:</b>	100000
<b>Beam angle [°]:</b>	114	<b>Light distribution type:</b>	lambertian
<b>Surge protection [kV]:</b>	2	<b>Warranty [years]:</b>	5
<b>Diffuser material:</b>	PS	<b>CE certificate:</b>	<a href="#">69/2026</a>
<b>Diffuser type:</b>	matt	<b>Environmental Product Declaration (EPD):</b>	<a href="#">869/2025</a>
<b>Diffuser colour:</b>	milky	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Optics material:</b>	PMMA	<b>ISO Certificates:</b>	9001:2015. 14001:2015. 45001:2018. 50001:2018

Card creation date: 09 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 69/2026