

CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	978883
Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	35
Luminous flux of the luminaire [lm] - range:	4450
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt

CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM 4450LM 840 IP40 II CL. MAT PS 35W DALI BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	978883	Colour of the body:	black
EAN:	5905963978883	Dimensions (H/W/T/S) [mm]:	400/400/39
Light source:	LED	Impact resistance:	IK07
Rated power [W] - range:	35	Ingress protection:	IP40
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50-60	Working temperature [°C]:	from 0 to +35
Luminous flux of the luminaire [lm] - range:	4450	DIMM DALI:	yes
Luminous efficacy [lm/W]:	127	Number on the palette [pcs]:	44
Energy efficiency class:	D	Net weight [kg]:	0.900
Electrical protection class:	II	LED lifespan L70B50 [h]:	50000
Colour temperature [K]:	4000	LED lifespan L80B10 [h]:	100000
Color rendering index (Ra) >:	80	Light distribution type:	lambertian
Beam angle [°]:	114	Warranty [years]:	5
Surge protection [kV]:	2	CE certificate:	69/2026
Diffuser material:	PS	Environmental Product Declaration (EPD):	869/2025
Diffuser type:	matt	Manual:	Download PDF
Diffuser colour:	milky	ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Optics material:	PMMA	Plik LDT:	Download
Material of the body:	coated aluminium		

Card creation date: 09 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 69/2026