# CONTRA LED 400MM 4665LM 840 IP40 II CL. MAT PS 35W DALI WHITE

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 978876 |
| **Ingress protection:** | IP40 |
| **Impact resistance:** | IK07 |
| **Rated power [W] - range:** | 35 |
| **Luminous flux of the luminaire [lm] - range:** | 4665 |
| **Color rendering index (Ra) >:** | 80 |
| **Energy efficiency class:** | D |
| **Material of the body:** | coated aluminium |
| **Diffuser material:** | PS |
| **Diffuser type:** | matt |

## CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

## APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

# CONTRA LED 400MM 4665LM 840 IP40 II CL. MAT PS 35W DALI WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 978876 |
| **EAN:** | 5905963978876 |
| **Light source:** | LED |
| **Rated power [W] - range:** | 35 |
| **Supply voltage [V]:** | 220-240 |
| **Frequency [Hz]:** | 50-60 |
| **Luminous flux of the luminaire [lm] - range:** | 4665 |
| **Luminous efficacy [lm/W]:** | 133 |
| **Energy efficiency class:** | D |
| **Electrical protection class:** | II |
| **Colour temperature [K]:** | 4000 |
| **Color rendering index (Ra) >:** | 80 |
| **Beam angle [°]:** | 114 |
| **Surge protection [kV]:** | 2 |
| **Diffuser material:** | PS |
| **Diffuser type:** | matt |
| **Diffuser colour:** | milky |
| **Optics material:** | PMMA |
| **Material of the body:** | coated aluminium |


| | |
|---|---|
| **Colour of the body:** | white |
| **Dimensions (H/W/T/S) [mm]:** | 400/400/39 |
| **Impact resistance:** | IK07 |
| **Ingress protection:** | IP40 |
| **Mounting version:** | surface |
| **Working temperature [°C]:** | from 0 to +35 |
| **DIMM DALI:** | yes |
| **Number on the palette [pcs]:** | 44 |
| **Net weight [kg]:** | 0.900 |
| **LED lifespan L70B50 [h]:** | 50000 |
| **LED lifespan L80B10 [h]:** | 100000 |
| **Light distribution type:** | lambertian |
| **Warranty [years]:** | 5 |
| **CE certificate:** | 69/2026 |
| **Environmental Product Declaration (EPD):** | 869/2025 |
| **Manual:** | Download PDF |
| **ISO Certificates:** | 9001:2015. 14001:2015. 45001:2018. 50001:2018 |
| **Plik LDT:** | Download |

# CONTRA LED 400MM 4665LM 840 IP40 II CL. MAT PS 35W DALI WHITE

DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 413995 | CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish |



CONTRA LED 400mm frame. ceiling grid. Raster 50x50xH22, RAL9005 matt black textured finish (413995)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 69/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl