

CONTRA LED 400MM 4665LM 840 IP40 II CL. MAT PS 35W DALI WHITE

DETAILED CARD



TECHNICAL PARAMETERS

Index:	978876
Ingress protection:	IP40
Impact resistance:	IK07
Rated power [W] - range:	35
Luminous flux of the luminaire [lm] - range:	4665
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	coated aluminium
Diffuser material:	PS
Diffuser type:	matt

CHARACTERISTICS

The Contra LED 400 MULTI is a versatile LED panel featuring a low, slim profile. Designed from the ground up, its construction incorporates innovative solutions that deliver excellent lighting performance. The body is made of aluminium, making it lightweight and highly impact-resistant (IK07). The opal diffuser, made of PS, ensures the luminaire has excellent lighting properties. The integrated LED module ensures low power consumption and all the benefits of modern LED luminaires. The multifunctional LED driver provides 4 brightness levels via a built-in switch. A version with a DALI driver is also available, enabling integration with lighting control systems and smooth dimming.

APPLICATION

Surface-mounted lamp for ceiling or wall mounting, intended for indoor use.

CONTRA LED 400MM 4665LM 840 IP40 II CL. MAT PS 35W DALI WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	978876	Material of the body:	coated aluminium
EAN:	5905963978876	Colour of the body:	white
Light source:	LED	Dimensions (H/W/T/S) [mm]:	400/400/39
Rated power [W] - range:	35	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP40
Frequency [Hz]:	50-60	Mounting version:	surface
Luminous flux of the luminaire [lm] - range:	4665	Working temperature [°C]:	from 0 to +35
Luminous efficacy [lm/W]:	133	DIMM DALI:	yes
Energy efficiency class:	D	Number on the palette [pcs]:	44
Electrical protection class:	II	Net weight [kg]:	0.900
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	50000
Color rendering index (Ra) >:	80	LED lifespan L80B10 [h]:	100000
Beam angle [°]:	114	Light distribution type:	lambertian
Surge protection [kV]:	2	Warranty [years]:	5
Diffuser material:	PS	CE certificate:	69/2026
Diffuser type:	matt	Environmental Product Declaration (EPD):	869/2025
Diffuser colour:	milky	Manual:	Download PDF
Optics material:	PMMA	ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018

Card creation date: 08 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 69/2026