

TERRACO AS PIR LED ALU PRM 1300LM IP54 I CL. 840 18W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	995781
Nominal power [W]:	18
Luminous flux [lm]*:	1300
Colour temperature [K]:	4000
Ingress protection:	IP54
Impact resistance:	IK04
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PMMA
Diffuser type:	PRM

CHARACTERISTICS

Terraco AS LED is a luminaire with a modernist structure, distinguished by its striking minimalist design. The powder-coated aluminium body is available in four colours: grey, graphite, white and black. It features a high IP54 protection rating. It is designed for surface mounting.

APPLICATION

The Terraco AS LED luminaire is particularly well-suited for external façade lighting, as well as for illuminating terraces and balconies. Its compact dimensions broaden its range of applications – it can illuminate recesses or hard-to-reach areas. Terraco luminaires can also be used indoors and arranged in various ways on walls to create interesting lighting schemes.

TERRACO AS PIR LED ALU PRM 1300LM IP54 I CL. 840 18W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	995781	Colour of the body:	black
EAN:	5905963995781	Dimensions (H/W/T/S) [mm]:	260/110/120
Light source:	LED module	Impact resistance:	IK04
Nominal power [W]:	18	Ingress protection:	IP54
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50-60	Working temperature [°C]:	from -25 to +35
Luminous flux [lm]:	1300	PIR:	yes
Luminous efficacy [lm/W]:	72	Number on the palette [pcs]:	120
Electrical protection class:	I	Net weight [kg]:	1.500
Colour temperature [K]:	4000	Gross weight [kg]:	1.200
Color rendering index (Ra) >:	80	Category type:	accent lighting
SDCM:	4	AC voltage range [V]:	220 - 240
Power factor:	0.99	LED lifespan L70B50 [h]:	134000
Exchangeable source:	yes	LED lifespan L80B10 [h]:	86000
Diffuser material:	PMMA	LED lifespan L90B10 [h]:	46000
Diffuser type:	PRM	Light distribution type:	DIR
Diffuser colour:	milky	Warranty [years]:	5
Optics:	general	CE certificate:	71/2026
Material of the body:	aluminium	Manual:	Download PDF

Card creation date: 21 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 71/2026