

LABO LED CLIP-IN 24MM 1200X300MM 8525LM 840 PLX IP65/IP20 67W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	302329
Ingress protection:	IP65/IP20
Rated power of the luminaire [W]*:	67
Luminous flux [lm]*:	8525
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	D
Diffuser material:	PMMA

CHARACTERISTICS

An IP65-rated LED luminaire, designed for demanding medical, laboratory and cleanroom environments. Labo LED combines high-quality light, reliability and a minimalist, easy-to-clean design, promoting safety and comfort in environments with stringent hygiene requirements.

Technical details:

The luminaire is compatible with the CLIP-IN ALVO mounting system, with a mounting tolerance of +/- 2mm.

APPLICATION

The luminaire is designed for indoor use in medical and laboratory facilities, as well as in industrial premises (particularly in the food, pharmaceutical and cosmetics industries), where high airtightness and the highest lighting performance are required.

LABO LED CLIP-IN 24MM 1200X300MM 8525LM 840 PLX IP65/IP20 67W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	302329	Diffuser material:	PMMA
EAN:	5905963302329	Diffuser type:	OPAL
Light source:	LED module	Colour of the body:	white
Rated power of the luminaire [W]:	67	Dimensions (H/W/T/S) [mm]:	1200/300/60
Supply voltage [V]:	220 - 240	Ingress protection:	IP65/IP20
Frequency [Hz]:	50 - 60	Mounting version:	Clip in 24mm
Luminous flux [lm]:	8525	Working temperature [°C]:	35
Luminous efficacy [lm/W]:	127	Net weight [kg]:	4.500
Energy efficiency class:	D	Category type:	troffers
Electrical protection class:	I	SDCM:	3
Colour temperature [K]:	4000	Warranty [years]:	5
Color rendering index (Ra) >:	80	CE certificate:	75/2026
LED lifespan L70B50 [h]:	153000	PZH certificate:	B-BK-60212-0111/21
LED lifespan L80B10 [h]:	100000	Manual:	Download PDF
LED lifespan L90B10 [h]:	50000	Plik LDT:	Download

LABO LED CLIP-IN 24MM 1200X300MM 8525LM 840 PLX IP65/IP20 67W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
374845	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635
WHITE (374845)

Card creation date: 28 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 75/2026