

FACTOR LED XL C5-M 2M 155000LM 840 20D DALI IP66 (1110W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	493515
Ingress protection:	IP66
Rated power of the luminaire [W]*:	1110
Luminous flux [lm]*:	155000
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	C
Warranty [years]:	5
Impact resistance:	IK09

CHARACTERISTICS

Very high-power floodlights used in the most demanding investments, professional sports facilities, football stadiums, where sporting events are broadcast by television in accordance with the highest standards. The prototype in the FACTOR family is the highly acclaimed FACTOR LED floodlight, consisting of 1-4 modules with a maximum luminous flux of approx. 150,000 lm. The new FACTOR XL series raises the bar by almost doubling the maximum luminous flux using only three modules and the highest luminous efficacy. All this is thanks to a compact and efficient design, which also translates into lower investment and operating costs for the facility. The exceptional quality of light is ensured by branded LEDs and professional optical systems. Excellent tightness and impact resistance parameters ensure operation in the most difficult weather conditions.

APPLICATION

Ports, quays, shipyards, drilling platforms and offshore infrastructure, chemical industry and refineries, bridges and infrastructure exposed to marine conditions, lighting on ships and ferries, industrial areas, sports fields, airports, car parks with high humidity and salinity. It can be used and works well both inside industrial, warehouse and sports halls, logistics centres, as well as outside – on sports fields, airports, car parks and manoeuvring areas. It can also illuminate building facades and external architectural elements.

FACTOR LED XL C5-M 2M 155000LM 840 20D DALI IP66 (1110W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	493515	LED lifespan L90B10 [h]:	1780000
EAN:	5905963493515	Beam angle [°]:	20
Light source:	LED module	Surge protection [kV]:	6
Rated power of the luminaire [W]:	1110	Diffuser material:	PC
Luminous flux [lm]:	155000	Diffuser type:	matrix led
Supply voltage [V]:	220-240	Material of the body:	aluminium
Luminous efficacy [lm/W]:	140	Colour of the body:	RAL7016
Energy efficiency class:	C	Dimensions (H/W/T/S) [mm]:	779/624/238
Electrical protection class:	I	Impact resistance:	IK09
Colour temperature [K]:	4000	Mounting version:	top
Color rendering index (Ra) >:	80	Working temperature [°C]:	from -40 to +35
Mounting dimensions [mm]:	302/79	Dimensions of single box [mm]:	783/630/238
Ingress protection:	IP66	Number on the palette [pcs]:	5
DIMM DALI:	yes	Net weight [kg]:	23.500
Version:	2M	Warranty [years]:	5
Light distribution type:	symmetric	CE certificate:	76/2026
Corrosivity category:	C5-M	ENEC Certificate:	0404/ENEC/25
Frequency [Hz]:	47-63	Environmental Product Declaration (EPD):	816/2025
LED lifespan L70B50 [h]:	520000	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
LED lifespan L80B10 [h]:	1110000	Manual:	Download PDF

Card creation date: 19 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 76/2026