

LUMEDIC 295X1195MM SW 7675LM RA80 4000K GLASS/PRM IP65 I CL. AW3H W IK09 R 47W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---------------------|
| Index: | 495403 |
| Ingress protection: | IP65 |
| Impact resistance: | IK09 |
| Rated power of the luminaire [W]*: | 47 |
| Luminous flux [lm]*: | 7932 |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 80 |
| Energy efficiency class: | C |
| Material of the body: | powder coated steel |
| Diffuser material: | szyba hartowana |

CHARACTERISTICS

Lumedic SW R this is a specialist cleanroom luminaire designed for cleanrooms with an air cleanliness class of ISO 3–9, in accordance with ISO 14644-1:2015 Cleanroom, and meeting stringent hygiene and sterility requirements. Its design ensures ease of cleaning and high mechanical and environmental resistance. A robust steel housing with IP65 protection on the room side and on the technical side ensures complete tightness in a sterile environment, while allowing free air flow above the suspended ceiling. Service access is provided from the technical side (top inspection), allowing maintenance without interfering with the clean room. The front of the luminaire is made of aluminium and 4 mm thick tempered glass, resistant to impact (IK09 class) and chemicals. The modular shutter system (Glass / Opal / PRM) allows you to select the appropriate optical characteristics depending on the application requirements — from uniform, diffused light to precise directional distribution. The SW R version is designed for installation in reinforced ceilings.

APPLICATION

- laboratories (microbiological, pharmaceutical, chemical),
- hospitals (operating theatres, intensive care units, diagnostic laboratories),
- food and pharmaceutical industry,
- cleanrooms in electronics and semiconductor manufacturing.

LUMEDIC 295X1195MM SW 7675LM RA80 4000K GLASS/PRM IP65 I CL. AW3H W IK09 R 47W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------------|---|---|
| Index: | 495403 | Mounting dimensions [mm]: | 285/1185 |
| EAN: | 5905963495403 | Impact resistance: | IK09 |
| Light source: | LED module | Ingress protection: | IP65 |
| Rated power of the luminaire [W]: | 47 | Mounting version: | recessed |
| Supply voltage [V]: | 220 - 240 | Working temperature [°C]: | from -20 to +35 |
| Frequency [Hz]: | 0/50/60 | Number on the palette [pcs]: | 16 |
| Luminous flux [lm]: | 7932 | Net weight [kg]: | 11 |
| Luminous efficacy [lm/W]: | 163 | Charging time [h:min]: | 16 |
| Energy efficiency class: | C | Battery life [h:min]: | 3 |
| Electrical protection class: | I | Battery: | Li-Ion |
| Colour temperature [K]: | 4000 | Battery capacity [mAh]: | 5000 |
| Color rendering index (Ra) >: | 80 | Emergency lighting [h]: | 3 |
| Power factor: | 0.95 | Autotest: | yes |
| Surge protection [kV]: | 1 | Operating mode: | yes |
| Diffuser material: | szyba hartowana | Warranty [years]: | 2 |
| Diffuser type: | Glass/PRM | CE certificate: | 89/2026 |
| Optics: | PRM | ENEC Certificate: | 0463/ENEC/25 |
| Material of the body: | powder coated steel | PZH certificate: | |
| Colour of the body: | biały Ral 9003 | Environmental Product Declaration (EPD): | 869/2025 |
| Ring material: | biały Ral 9003 | Manual: | Download PDF |
| Ring colour: | biały Ral 9003 | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018, ISO 3 - 9 (ISO 14644-1:2015) |
| Dimensions (H/W/T/S) [mm]: | 295/1195/65 | | |

Card creation date: 10 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 89/2026