

# SQ 300 LED EVO PLUS 3000LM 830 IP54 II CL. OPAL (31W) 300MM

DETAILED CARD



## TECHNICAL PARAMETERS

|   |        |
|---|--------|
| <b>Index:</b>                             | 729690 |
| <b>Ingress protection:</b>                | IP54   |
| <b>Impact resistance:</b>                 | IK08   |
| <b>Rated power of the luminaire [W]*:</b> | 31     |
| <b>Luminous flux [lm]*:</b>               | 3000   |
| <b>Colour temperature [K]:</b>            | 3000   |
| <b>Color rendering index (Ra) &gt;:</b>   | 80     |
| <b>SDCM:</b>                              | 3      |
| <b>Energy efficiency class:</b>           | F      |
| <b>Material of the body:</b>              | ABS    |

## CHARACTERISTICS

Is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

## APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.


# SQ 300 LED EVO PLUS 3000LM 830 IP54 II CL. OPAL (31W) 300MM

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                                |   |
|-----------------------------------|---------------|--------------------------------|---|
| Index:                            | 729690        | Dimensions (H/W/T/S) [mm]:     | 300/300/58  |
| EAN:                              | 5905963729690 | Mounting dimensions [mm]:      | 210   |
| Rated power of the luminaire [W]: | 31            | Impact resistance:             | IK08  |
| Supply voltage [V]:               | 220 - 240     | Ingress protection:            | IP54  |
| Frequency [Hz]:                   | 50-60         | Mounting version:              | surface   |
| Luminous flux [lm]:               | 3000          | Working temperature [°C]:      | from -20 to +35   |
| Luminous efficacy [lm/W]:         | 97            | Dimensions of single box [mm]: | 305/305/60  |
| Energy efficiency class:          | F             | Number on the palette [pcs]:   | 120   |
| Electrical protection class:      | II            | Net weight [kg]:               | 0.750   |
| Colour temperature [K]:           | 3000          | Category type:                 | bulkheads   |
| Color rendering index (Ra) >:     | 80            | Category of application:       | educational institutions, HoReCa, commercial facilities |
| SDCM:                             | 3             | AC voltage range [V]:          | 220 - 240   |
| Power factor:                     | 0.98          | LED lifespan L70B50 [h]:       | 118000  |
| Beam angle [°]:                   | 120           | LED lifespan L80B10 [h]:       | 75000   |
| Surge protection [kV]:            | 1             | LED lifespan L90B10 [h]:       | 36000   |
| Diffuser material:                | PS            | Light distribution type:       | open space  |
| Diffuser type:                    | OPAL          | Photobiological safety:        | RG0 - exempt (no photobiological hazard)                |
| Diffuser colour:                  | white         | Warranty [years]:              | 5   |
| Optics material:                  | PMMA          | CE certificate:                | <a href="#">97/2026</a>                                 |
| Material of the body:             | ABS           | ENEC Certificate:              | 0316/ENEC/29  |
| Colour of the body:               | white         | Manual:                        | <a href="#">Download PDF</a>                            |

## LIGHT CURVES



Card creation date: 18 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 97/2026



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)