

TIARA 2 LED L 48400LM 740 RM7HE IP66 II CL. DALI IK10 (320W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	823572
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	320
Luminous flux [lm]*:	48403
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
Electrical protection class:	II
Optics:	RM7HE
Control:	Yes + 5-stage power reduction

CHARACTERISTICS

TIARA 2 LED L a family of LED road luminaires based on a proven form factor. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and new LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 181 lm/W. The two-chamber construction of the luminaire maintains the tightness of the optical chamber during assembly work and allows tool-free access to the electrical equipment chamber. The upper part of the luminaire, has dedicated hinges and a safety cord. Using standard tools, quick and convenient servicing is possible, allowing the replacement of any component without having to dismantle the entire luminaire and make soldered connections. The body and handle are made of die-cast aluminium, powder-coated grey, and have a very high IP66 protection rating and IK09 mechanical impact resistance. Standard features: ergonomic light module suspension system; fully programmable DALI driver; CLO constant lumen maintenance and autonomous 5-stage power reduction functions available; NTC overheating protection; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnecter to disconnect voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: motorways, motorways, national roads, voivodeships, districts, communes, municipalities, housing estates, area lighting. Optics are also available to illuminate: pedestrian crossings, pavements and cycle paths.


TIARA 2 LED L 48400LM 740 RM7HE IP66 II CL. DALI IK10 (320W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	823572	Material of the body:	powder coated aluminium
EAN:	5905963823572	Colour of the body:	grey
Category type:	street lighting	Dimensions (H/W/T/S) [mm]:	839/113/265
Category of application:	Street lighting	Mounting dimensions [mm]:	ø40-60
Product line:	HE	Impact resistance:	IK10
Version:	L	Ingress protection:	IP66
Light source:	LED module	Mounting version:	Top, on pole / Side, on boom
Rated power of the luminaire [W]:	320	Lateral surface (SCx) [m2]:	0.029
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -40 to +50
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	48403	Control:	Yes + 5-stage power reduction
Luminous efficacy [lm/W]:	151	Protection type:	NTC + ESD
Energy efficiency class:	C	Net weight [kg]:	6.500
Electrical protection class:	II	ULOR:	0%
Colour temperature [K]:	4000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Color rendering index (Ra) >:	70	Technical Warranty:	5 with the possibility of extension to 10
SDCM:	5	ENEC Certificate:	0449/ENEC/25; 0163/ENEC+25
Power factor:	1	CE certificate:	127/2025
Surge protection [kV]:	10	Zhaga-D4i:	ZG407420042023
Diffuser material:	szkło hartowane 5mm	Environmental Product Declaration (EPD):	682/2024
Diffuser type:	transparent	Manual:	Download PDF
Optics material:	PMMA + PC	LED lifespan L95B10 [h]:	100000
Optics:	RM7HE	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Exchangeable source:	yes		

LIGHT CURVES



TIARA 2 LED L 48400LM 740 RM7HE IP66 II CL. DALI IK10 (320W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00184	mounting grip 78 mm TIARA LED
989766	Tiara 2 LED 64mm handle cover



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm TIARA
LED (UL00184)



Tiara 2 LED 64mm handle
cover (989766)

Card creation date: 25 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 127/2025