

# CAPELLA LED BOX 320MM 1300LM IP54 RCR 830 (15W)

DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP54
Nominal power [W]:	15
Luminous flux [lm]*:	1300
Colour temperature [K]:	3000
SDCM:	≤ 4
Energy efficiency class:	F
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	320/105

## CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

## APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


# CAPELLA LED BOX 320MM 1300LM IP54 RCR 830 (15W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ring material:	ABS
Nominal power [W]:	15	Dimensions (H/W/T/S) [mm]:	320/105
Rated power of the luminaire [W]:	16	Mounting dimensions [mm]:	160
Supply voltage [V]:	220 - 240	Impact resistance:	IK06
Frequency [Hz]:	50 - 60	Ingress protection:	IP54
Source luminous flux [lm]*:	1828	Mounting version:	surface
Luminous flux [lm]:	1300	Working temperature [°C]:	from -10 to +35
Luminous efficacy [lm/W]:	81	Motion sensor:	yes
Energy efficiency class:	F	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Electrical protection class:	II	Dimensions of single box [mm]:	342/342/122
Colour temperature [K]:	3000	Net weight [kg]:	0.725
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 4	CE certificate:	<a href="#">105/2018</a>
Power factor:	0.50	Index:	949753
LED lifespan L70B50 [h]:	88000	EAN:	5905963949753
Beam angle [°]:	120	Category type:	bulkheads
Diffuser material:	PC	Version:	BOX
Diffuser type:	OPAL	Max load (RCR) [W]:	300
Diffuser colour:	white	Product line:	standard
Material of the body:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



Card creation date: 10 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 105/2018



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)