CAPELLA LED BOX RING 320MM 880LM IP54 840 (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Nominal power [W]:	9
Luminous flux [lm]*:	880
Colour temperature [K]:	4000
SDCM:	≤ 4
Energy efficiency class:	F
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	340/105

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED BOX RING 320MM 880LM IP54 840 (9W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	9
Rated power of the luminaire [W]:	11
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Source luminous flux [lm]*:	1202
Luminous flux [lm]:	880
Luminous efficacy [lm/W]:	80
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 4
Power factor:	0.50
LED lifespan L70B50 [h]:	88000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	ABS
Colour of the body:	white

Ring material:	ABS
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	340/105
Mounting dimensions [mm]:	160
Impact resistance:	IK07
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -10 to +35
Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Dimensions of single box [mm]:	342/342/122
Net weight [kg]:	0.780
Warranty [years]:	5
CE certificate:	105/2018
Index:	949814
EAN:	5905963949814
Category type:	bulkheads
Version:	BOX RING
Product line:	standard
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Manual:	Download PDF

LIGHT CURVES



Card creation date: 10 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 105/2018

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl