OVAL LED 3W SIMETAL POPIELATY 4000K

DETAILED CARD





TECHNICAL PARAMETERS

Index:	233067
Ingress protection:	IP44/40
Impact resistance:	IK06
Nominal power [W]:	2.50
Luminous flux [lm]*:	210
Colour temperature [K]:	4000
Energy efficiency class:	G
Material of the body:	PP
Diffuser material:	glass
Diffuser type:	PRM

CHARACTERISTICS

Surface-mounted, oval channel-type LED fitting with ingress protection class IP44 and an integrated energy-saving light source LED. Polypropylene base; prismatic glass diffuser. Fitting is available in two power versions and six base colors. Also available are numerous special-purpose versions: a 24V fitting or fittings that can be used as marker lights (Oval LED RED equipped with red-colored diodes and Oval LED BLUE equipped with blue-colored diodes).

APPLICATION

Surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial façade lighting, parking lots). The 24V version is particularly well-suited to be used as a light source for public rooms and buildings (civic buildings, apartment buildings).

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%





This product is a subject to electric and electronic waste equipment regulations (WEEE).

OVAL LED 3W SIMETAL POPIELATY 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	2.50
Rated power of the luminaire [W]:	3
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	210
Luminous efficacy [lm/W]:	70
Energy efficiency class:	G
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
LED lifespan L70B50 [h]:	80 000
Beam angle [°]:	120
Diffuser material:	glass
Diffuser type:	PRM
Material of the body:	PP
Colour of the body:	gray

	•
Dimensions (H/W/T/S) [mm]:	125/170/105
Impact resistance:	IK06
Ingress protection:	IP44/40
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.500
Index:	233067
EAN:	5905963233067
Category type:	bulkheads
Warranty [years]:	5
CE certificate:	400/2023
ETIM class:	EC001058
Mounting dimensions [mm]:	110
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES

