

FRAGA LED 11W 36ST 3000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	059247
Ingress protection:	IP43/20
Nominal power [W]:	11
Luminous flux [lm]*:	640
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	G
Material of the body:	aluminium, PMMA
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

A downlight luminaire with narrow, 36° wide, light distribution angle and the light beam adjustable within +/-30°. Equipped with modern and energy-efficient COB LED light source. Its body made of aluminium and PMMA ensures optimum LED operating conditions and the diffuser made of highly transparent PMMA guarantees high luminous efficiency of the luminaire. Suitable for tool-free installation in plasterboard ceilings.

APPLICATION

Intended for indoor use in passageways and entry areas.


FRAGA LED 11W 36ST 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	white
Nominal power [W]:	11	Dimensions (H/W/T/S) [mm]:	ø109/60
Rated power of the luminaire [W]:	11	Mounting dimensions [mm]:	ø95
Supply voltage [V]:	220-240	Impact resistance:	IK08
Frequency [Hz]:	50 - 60	Ingress protection:	IP43/20
Luminous flux [lm]:	640	Mounting version:	recessed
Luminous efficacy [lm/W]:	58	Net weight [kg]:	0.290
Energy efficiency class:	G	CE certificate:	352/2023
Electrical protection class:	II	Warranty [years]:	5
Colour temperature [K]:	3000	Index:	059247
Colour rendering index:	>80	EAN:	5905963059247
LED lifespan L70B50 [h]:	50000	Category type:	downlights
Beam angle [°]:	120	ETIM class:	EC002892
Diffuser material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	PRM	Manual:	Download PDF
Material of the body:	aluminium, PMMA		

LIGHT CURVES



FRAGA LED 11W 36ST 3000K

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
059858	Round surface casing - white. 15W
059841	Round surface casing white NECTRA LED IP44 5W. NECTRA LED 5W. 7W, FRAGA LED 11W
060922	Round surface casing white NECTRA LED IP44 9W. NECTRA LED 7W, FRAGA 11W



Round surface casing - white.
15W (059858)



Round surface casing white NECTRA
LED IP44 5W. NECTRA LED 5W. 7W,
FRAGA LED 11W (059841)



Round surface casing white NECTRA
LED IP44 9W. NECTRA LED 7W,
FRAGA 11W (060922)

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 352/2023