# VEGA LED 880 LM 840 IP44 I KL. OPAL WHITE 7W

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

950537
IP44
IK08
7
880
4000
≤ 5
Е
PP
glass

### **CHARACTERISTICS**

LED light fixture with integrated energy-saving light source LED GO! and high ingress protection class IP44. Base made of UV-resistant plastic. Diffuser made of PC, available in 2 versions: opalized or prismatic.

## **APPLICATION**

Surface mounted fitting with an ingress protection class of IP54 dedicated for both outdoor and indoor use.



# VEGA LED 880 LM 840 IP44 I KL. OPAL WHITE 7W

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Light source:	LED module
Nominal power [W]:	7
Rated power of the luminaire [W]:	8.40
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	880
Luminous efficacy [lm/W]:	97
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 5
Power factor:	0.99
LED lifespan L70B50 [h]:	80000
Beam angle [°]:	120
Diffuser material:	glass
Diffuser type:	OPAL

Material of the body:	PP
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	239/95
Impact resistance:	IK08
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.840
Warranty [years]:	5
Index:	950537
EAN:	5905963950537
Category type:	bulkheads
Luminaire rated power 0min [W]:	9
Category of application:	parkings and bicycle paths
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
Manual:	Download PDF

Card creation date: 01 April 2020



