VEGA LED 920 LM 840 IP44 I KL. PRM WHITE 7W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	950520
Ingress protection:	IP44
Impact resistance:	IK08
Nominal power [W]:	7
Luminous flux [lm]*:	920
Colour temperature [K]:	4000
SDCM:	≤ 5
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	glass

CHARACTERISTICS

LED light fixture with integrated energy-saving light source LED GO! and high ingress protection class IP44. Base made of UV-resistant plastic. Diffuser made of PC, available in 2 versions: opalized or prismatic.

APPLICATION

Surface mounted fitting with an ingress protection class of IP54 dedicated for both outdoor and indoor use.



VEGA LED 920 LM 840 IP44 I KL. PRM WHITE 7W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	white
Nominal power [W]:	7	Dimensions (H/W/T/S) [mm]:	239/95
Rated power of the luminaire [W]:	9	Impact resistance:	IK08
Supply voltage [V]:	220-240	Ingress protection:	IP44
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [Im]:	920	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	103	Net weight [kg]:	0.840
Energy efficiency class:	E	Warranty [years]:	5
Electrical protection class:	1	Index:	950520
Colour temperature [K]:	4000	EAN:	5905963950520
Colour rendering index:	80	Category type:	bulkheads
SDCM:	≤ 5	Luminaire rated power Omin [W]:	8.40
Power factor:	0.99	Category of application:	parkings and bicycle paths
LED lifespan L70B50 [h]:	80000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral
Beam angle [°]:	120		limitation)
Diffuser material:	glass	Warranty [years]:	2
Diffuser type:	PRM	Manual:	Download PDF
Material of the body:	PP	CE certificate:	<u>394/2023</u>

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This produ





Certificate CE - Nr: 394/2023