

# DLN 220 LED EVO LV 220MM 1500LM 840 PRM (10W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	554360
<b>Ingress protection:</b>	IP65
<b>Nominal power [W]:</b>	10
<b>Luminous flux [lm]*:</b>	1500
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	powder coated steel
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Surface-mounted downlight with an integrated energy-saving LED panel, with high ingress protection class IP65 and high impact protection class IK08. Opal diffuser made of polycarbonate ensures even light distribution.

## APPLICATION

The fitting is intended for surface mounting. High ingress protection class IP65 and high impact protection class make it suitable for outdoor use. Small parameters and timeless design will also prove useful in offices, passageways and administrative buildings.

# DLN 220 LED EVO LV 220MM 1500LM 840 PRM (10W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø220/140
Nominal power [W]:	10	Mounting dimensions [mm]:	ø90
Rated power of the luminaire [W]:	12.20	Impact resistance:	IK08
Supply voltage [V]:	220-240	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	1500	Working temperature [°C]:	from -15 to +35
Luminous efficacy [lm/W]:	122	Net weight [kg]:	1.710
Energy efficiency class:	D	Gross weight [kg]:	2.550
Electrical protection class:	I	Index:	554360
Colour temperature [K]:	4000	EAN:	5905963554360
Color rendering index (Ra) >:	80	Category type:	downlights
SDCM:	3	Luminaire rated power Omin [W]:	12
Power factor:	0.91	LED lifespan L80B10 [h]:	73000
LED lifespan L70B50 [h]:	117000	LED lifespan L90B10 [h]:	34000
Beam angle [°]:	120	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	PRM	CE certificate:	<a href="#">333/2023</a>
Diffuser colour:	transparent	ENEC Certificate:	<a href="#">0346/ENEC/24</a>
Material of the body:	powder coated steel	Manual:	<a href="#">Download PDF</a>
Colour of the body:	grey	Plik LDT:	<a href="#">Download</a>

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 333/2023