

DLN 220 LED EVO LV 220MM 3450LM 840 PRM (28W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	554421
Ingress protection:	IP65
Nominal power [W]:	28
Luminous flux [lm]*:	3450
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	powder coated steel
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

Surface-mounted downlight with an integrated energy-saving LED panel, with high ingress protection class IP65 and high impact protection class IK08. Opal diffuser made of polycarbonate ensures even light distribution.

APPLICATION

The fitting is intended for surface mounting. High ingress protection class IP65 and high impact protection class make it suitable for outdoor use. Small parameters and timeless design will also prove useful in offices, passageways and administrative buildings.

DLN 220 LED EVO LV 220MM 3450LM 840 PRM (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	Mounting dimensions [mm]:	ø90
Light source:	LED module	Impact resistance:	IK08
Colour temperature [K]:	4000	Ingress protection:	IP65
Luminous flux [lm]:	3450	Mounting version:	surface
Rated power of the luminaire [W]:	29.30	Working temperature [°C]:	from -15 to +35
Diffuser type:	PRM	Net weight [kg]:	1.660
Supply voltage [V]:	220-240	Gross weight [kg]:	2.550
Luminous efficacy [lm/W]:	117	Index:	554421
Energy efficiency class:	D	EAN:	5905963554421
Electrical protection class:	I	Category type:	downlights
Colour rendering index:	>80	Luminaire rated power O_{min} [W]:	30.40
SDCM:	≤ 3	LED lifespan L80B20 [h]:	73000
Power factor:	0.96	LED lifespan L90B10 [h]:	34000
LED lifespan L70B50 [h]:	117000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	333/2023
Diffuser colour:	transparent	ENEC Certificate:	0346/ENEC/24
Material of the body:	powder coated steel	Manual:	Download PDF
Colour of the body:	grey	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	ø220/140		

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 333/2023