

# POXAR SN-F LED

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	324543
Ingress protection:	IP40
Nominal power [W]:	1
Material of the body:	PC
Diffuser material:	PMMA
Emergency lighting [h]:	3
Working temperature [°C]:	from 0 to +35
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	299/206/43

## CHARACTERISTICS

Surface mounted emergency fitting with a power of 1W, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, battery life in the event of emergency is 3h. NiCd battery life in the event of emergency is 3h. A bracket for wall mounting available on request.

## APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended in for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

# POXAR SN-F LED

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Nominal power [W]:	1	Mounting version:	surface
Light source:	LED module	Working temperature [°C]:	from 0 to +35
Emergency lighting [h]:	3	Net weight [kg]:	0.850
Supply voltage [V]:	220-240	CE certificate:	<a href="#">68/2020</a>
Frequency [Hz]:	50 - 60	Warranty [years]:	2 / 0.5 (bateria)
Electrical protection class:	II	Index:	324543
LED lifespan L70B50 [h]:	50000	EAN:	5905963324543
Beam angle [°]:	120	Category type:	emergency lighting
Diffuser material:	PMMA	ETIM class:	EC002892
Material of the body:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	299/206/43	Manual:	<a href="#">Download PDF</a>
Ingress protection:	IP40		