

POXAR SN-F LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	324543
Ingress protection:	IP40
Nominal power [W]:	1
Material of the body:	PC
Diffuser material:	PMMA
Emergency lighting [h]:	3
Working temperature [°C]:	from 0 to +35
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	299/206/43

CHARACTERISTICS

Surface mounted emergency fitting with a power of 1W, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, battery life in the event of emergency is 3h. NiCd battery life in the event of emergency is 3h. A bracket for wall mounting available on request.

APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended in for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

POXAR SN-F LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Working temperature [°C]:	from 0 to +35
Nominal power [W]:	1	Emergency lighting [h]:	3
Supply voltage [V]:	220-240	Net weight [kg]:	0.850
Frequency [Hz]:	50 - 60	CE certificate:	68/2020
Electrical protection class:	II	Warranty [years]:	2 / 0.5 (bateria)
LED lifespan L70B50 [h]:	50000	Index:	324543
Beam angle [°]:	120	EAN:	5905963324543
Diffuser material:	PMMA	Category type:	emergency lighting
Material of the body:	PC	ETIM class:	EC002892
Dimensions (H/W/T/S) [mm]:	299/206/43	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ingress protection:	IP40	Manual:	Download PDF
Mounting version:	surface		