INDO LED PLX 34W 3000K

DETAILED CARD





TECHNICAL PARAMETERS

Index:	380235
Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	34
Luminous flux [lm]*:	3000
Colour rendering index:	>80
SDCM:	≤3
Energy efficiency class:	F
Material of the body:	powder coated steel
Diffuser material:	PMMA

CHARACTERISTICS

Recessed mounted square luminaire with an integrated energysaving LED GO! light source. Powder-coated steel body. The lens diffuser is made of perforated metal sheet. It provides comfortable and soft light.

APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. Suitable as a general light source for all sorts of work that require optical focus. Dedicated for new applications and as a replacement of traditional T8 and T5 tube luminaires with energy-saving LED lamps.




INDO LED PLX 34W 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	34	Optics material:	РММА
Index:	380235	Material of the body:	powder coated steel
Colour temperature [K]:	3000	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	595/595/105
Luminous flux [Im]:	3000	Impact resistance:	IK07
Diffuser type:	OPAL	Ingress protection:	IP20
Rated power of the luminaire [W]:	34	Mounting version:	recessed
Energy efficiency class:	F	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Net weight [kg]:	3.750
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Luminous efficacy [lm/W]:	88	CE certificate:	<u>35/2016</u>
Electrical protection class:	I	EAN:	5905963380235
Colour rendering index:	>80	Category type:	louvres
SDCM:	≤3	ETIM class:	EC002892
Power factor:	0.95	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral
LED lifespan L70B50 [h]:	50000	Photobiological safety:	limitation)
Diffuser material:	РММА	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES





DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)

Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 35/2016

This product is a subject to electric and electronic waste equipment regulations (WEEE).



A