CAMEA PRO LED EVO 11W MAT BIAŁA 3000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	206047/HV
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	11
Luminous flux [lm]*:	1000
Colour temperature [K]:	3000
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted round LED bulkhead with integrated, energy-saving light source LED GO!, high luminous flux and ingress protection class IP44 . Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). The luminaire made in an anti-theft version with an additional protective ring. Available option with a radio motion sensor (RCR).

APPLICATION

Surface mounted luminaire for ceiling or wall installation, dedicated for indoor use - in general utility rooms, passageways, staircases. Available option with a radio motion sensor (RCR), which is particularly recommended for use in public areas

CAMEA PRO LED EVO 11W MAT BIAŁA 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	11
Rated power of the luminaire [W]:	11
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1000
Luminous efficacy [lm/W]:	91
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	>80
Power factor:	0.53
LED lifespan L70B50 [h]:	50000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	PP

Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	ø300/90
Impact resistance:	IK10
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.600
CE certificate:	56/2015
Index:	206047/HV
EAN:	5905963206047/HV
Category type:	bulkheads
ETIM class:	EC002892
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
Luminaire rated power 0min [W]:	11
Manual:	Download PDF

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 56/2015

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl