CAMEA PRO LED EVO 11W MAT BIAŁA 4000K

DETAILED CARD





TECHNICAL PARAMETERS

Index:	206054/HV
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	11
Luminous flux [lm]*:	1080
Colour temperature [K]:	4000
Energy efficiency class:	Е
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted round LED bulkhead with integrated, energy-saving light source LED GO!, high luminous flux and ingress protection class IP44. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). The luminaire made in an anti-theft version with an additional protective ring. Available option with a radio motion sensor (RCR).

APPLICATION

Surface mounted luminaire for ceiling or wall installation, dedicated for indoor use - in general utility rooms, passageways, staircases. Available option with a radio motion sensor (RCR), which is particularly recommended for use in public areas



CAMEA PRO LED EVO 11W MAT BIAŁA 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	11
Rated power of the luminaire [W]:	11
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	1080
Luminous efficacy [lm/W]:	98
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Colour rendering index:	>80
Power factor:	0.53
LED lifespan L70B50 [h]:	50000
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	PP

Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	ø300/90
Impact resistance:	IK10
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.600
CE certificate:	<u>56/2015</u>
Index:	206054/HV
EAN:	5905963206054/HV
Category type:	bulkheads
ETIM class:	EC002892
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
Luminaire rated power 0min [W]:	11
Manual:	Download PDF

Card creation date: 06 December 2018



