

CAMEA PRO LED EVO 11W MAT BIAŁA RCR 3000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	10
Luminous flux [lm]*:	1000 - 2050
Colour temperature [K]:	3000; 4000
Energy efficiency class:	E; F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted round LED bulkhead with integrated, energy-saving light source LED GO!, high luminous flux and ingress protection class IP44 . Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). The luminaire made in an anti-theft version with an additional protective ring. Available option with a radio motion sensor (RCR).

APPLICATION

Surface mounted luminaire for ceiling or wall installation, dedicated for indoor use - in general utility rooms, passageways, staircases. Available option with a radio motion sensor (RCR), which is particularly recommended for use in public areas

CAMEA PRO LED EVO 11W MAT BIAŁA RCR 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Dimensions (H/W/T/S) [mm]:	ø300/90
Nominal power [W]:	10	Impact resistance:	IK10
Rated power of the luminaire [W]:	11	Ingress protection:	IP44
Supply voltage [V]:	220-240	Mounting version:	natynkowy
Frequency [Hz]:	50-60	Working temperature [°C]:	od -20 do +35
Luminous flux [lm]:	1000 - 2050	Motion sensor:	yes
Energy efficiency class:	E; F	Net weight [kg]:	0.600; 0.670
Electrical protection class:	II	CE certificate:	56/2015
Colour temperature [K]:	3000; 4000	Index:	x
Colour rendering index:	>80	EAN:	x
Power factor:	0.52; 0.53	Category type:	bulkheads
LED lifespan L70B50 [h]:	50000	ETIM class:	EC002892
Beam angle [°]:	120	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Diffuser material:	PC	Warranty [years]:	2
Diffuser type:	OPAL	Luminaire rated power 0min [W]:	11
Material of the body:	PP	Manual:	Download PDF
Colour of the body:	biały		

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 56/2015



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl