

CAMEA PRO LED EVO 20W MAT BIAŁA 4000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	206092/HV
Ingress protection:	IP44
Impact resistance:	IK10
Nominal power [W]:	20
Luminous flux [lm]*:	2050
Colour temperature [K]:	4000
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted round LED bulkhead with integrated, energy-saving light source LED GO!, high luminous flux and ingress protection class IP44 . Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). The luminaire made in an anti-theft version with an additional protective ring. Available option with a radio motion sensor (RCR).

APPLICATION

Surface mounted luminaire for ceiling or wall installation, dedicated for indoor use - in general utility rooms, passageways, staircases. Available option with a radio motion sensor (RCR), which is particularly recommended for use in public areas

CAMEA PRO LED EVO 20W MAT BIAŁA 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	white
Nominal power [W]:	20	Dimensions (H/W/T/S) [mm]:	ø300/90
Rated power of the luminaire [W]:	21	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP44
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	2050	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	97	Net weight [kg]:	0.600
Energy efficiency class:	E	CE certificate:	56/2015
Electrical protection class:	II	Index:	206092/HV
Colour temperature [K]:	4000	EAN:	5905963206092/HV
Colour rendering index:	>80	Category type:	bulkheads
Power factor:	0.52	ETIM class:	EC002892
LED lifespan L70B50 [h]:	50000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	Warranty [years]:	2
Diffuser material:	PC	Luminaire rated power Omin [W]:	21
Diffuser type:	OPAL	Manual:	Download PDF
Material of the body:	PP		