CAMEA PRO LED EVO 20W MAT BIAŁA RCR 4000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	206214/HV	
Ingress protection:	IP44	
Impact resistance:	IK10	
Nominal power [W]:	20	
Luminous flux [lm]*:	2050	
Colour temperature [K]:	4000	
Energy efficiency class:	E	
Material of the body:	PP	
Diffuser material:	PC	
Diffuser type:	OPAL	

CHARACTERISTICS

Surface mounted round LED bulkhead with integrated, energysaving light source LED GO!, high luminous flux and ingress protection class IP44 . Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). The luminaire made in an anti-theft version with an additional protective ring. Available option with a radio motion sensor (RCR).

APPLICATION

Surface mounted luminaire for ceiling or wall installation, dedicated for indoor use - in general utility rooms, passageways, staircases. Available option with a radio motion sensor (RCR), which is particularly recommended for use in public areas



CAMEA PRO LED EVO 20W MAT BIAŁA RCR 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

			1
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	20	Dimensions (H/W/T/S) [mm]:	ø300/90
Rated power of the luminaire [W]:	21	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP44
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	2050	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	98	Motion sensor:	yes
Energy efficiency class:	E	Net weight [kg]:	0.670
Electrical protection class:	н	CE certificate:	<u>56/2015</u>
Colour temperature [K]:	4000	Index:	206214/HV
Colour rendering index:	>80	EAN:	5905963206214/HV
Power factor:	0.52	Category type:	bulkheads
LED lifespan L70B50 [h]:	50000	ETIM class:	EC002892
Beam angle [°]:	120	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral
Diffuser material:	PC		limitation)
Diffuser type:	OPAL	Warranty [years]:	2
Material of the body:	PP	Luminaire rated power Omin [W]:	21
		Manual:	Download PDF

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 56/2015

A



This product is a subject to electric and electronic waste equipment regulations (WEEE).

Lena Lighting S.A. ul. Kórnicka 52, 63-000 Środa Wielkopolska tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl