

# QUEST LED EVO S 10250LM DALI I CL. IP67 740 120D 57W

## DETAILED CARD



### TECHNICAL PARAMETERS

|                                    |           |
|------------------------------------|-----------|
| Index:                             | 102943    |
| Ingress protection:                | IP67      |
| Impact resistance:                 | IK10      |
| Rated power of the luminaire [W]*: | 57        |
| Luminous flux [lm]*:               | 10250     |
| Colour temperature [K]:            | 4000      |
| Color rendering index (Ra) >:      | 70        |
| Electrical protection class:       | I         |
| Energy efficiency class:           | A         |
| Material of the body:              | aluminium |

### CHARACTERISTICS

The Quest LED Evo S is a member of a well-established family of high-bay luminaires, positioned in terms of size between the XS and M versions. It responds to market needs by filling a gap in the extremely popular segment of high-bay luminaires with a power rating of around 100 W. Together with the dedicated industrial High-Bay variants – the surface-mounted Quest LED Evo S HB NT and the recessed Quest LED Evo S HB Z – it forms a versatile range of premium-class luminaires, manufactured in Poland. The die-cast aluminium body is powder-coated. The design, which lacks external heat sink fins, prevents the build-up of dirt and makes maintenance much easier. The luminaire is designed for use in the most demanding environments (marine corrosion class C5-M as standard). It features the highest IP67 protection rating and the highest impact resistance rating of IK10. High-efficiency LEDs covered by tempered glass ensure a luminous efficacy exceeding 170 lm/W. A wide range of optical systems (including asymmetrical optics) guarantees a perfect match for the light distribution. Compliance with the PN-EN 60598-2 Part 5 standard classifies the luminaire as an architectural spotlight, allowing installation in any position, full 360° rotation and high resistance to wind gusts. The use of a sealed quick-connect coupler with intuitive, colour-coded latches reduces connection time and eliminates time-consuming traditional methods. The accessory kit includes pole-mounting brackets, a frame for flush-mounted installation (e.g. in canopies), light pollution control screens, and protective grilles in two colours with different levels of light reduction (white RAL7016: 4%, in the same colour as the body RAL7016: 8%). The models can be fitted with an external motion and twilight sensor. They are also available in the ENDURA version, which is resistant to elevated ambient temperatures of up to 50°C. DALI versions are available (if the specific wattage you require is not available with a DALI power supply, please check the ENDURA DALI versions).

### APPLICATION

The Quest LED EVO S is widely used for lighting educational, childcare and administrative facilities, halls, garages, passageways, warehouses, shops, as well as in the food industry and retail and service premises dealing with foodstuffs. They are the ideal solution for small sports pitches, open spaces and car parks. They can be installed as floodlights on poles and masts, on building façades, as well as surface-mounted high-bay luminaires (HB NT version) and suspended high-bay luminaires (HB Z version). Thanks to the recessed mounting option, they are ideal for use in canopies. The Quest LED EVO S is an excellent choice for factories, production halls and large-scale warehouses.

# QUEST LED EVO S 10250LM DALI I CL. IP67 740 120D 57W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                                          |                                                                             |
|-----------------------------------|---------------|------------------------------------------|-----------------------------------------------------------------------------|
| Index:                            | 102943        | Optics:                                  | lens                                                                        |
| EAN:                              | 5905963102943 | Material of the body:                    | aluminium                                                                   |
| Light source:                     | LED module    | Colour of the body:                      | RAL7016                                                                     |
| Rated power of the luminaire [W]: | 57            | Impact resistance:                       | IK10                                                                        |
| Supply voltage [V]:               | 220-240       | Ingress protection:                      | IP67                                                                        |
| Frequency [Hz]:                   | 0/50-60       | DIMM DALI:                               | yes                                                                         |
| Luminous flux [lm]:               | 10250         | Category type:                           | floodlights                                                                 |
| Luminous efficacy [lm/W]:         | 180           | Photobiological safety:                  | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Energy efficiency class:          | A             | Warranty [years]:                        | 5                                                                           |
| Electrical protection class:      | I             | CE certificate:                          | <a href="#">106/2026</a>                                                    |
| Colour temperature [K]:           | 4000          | ENEC Certificate:                        | <a href="#">0487/ENEC/26</a>                                                |
| Color rendering index (Ra) >:     | 70            | Environmental Product Declaration (EPD): | <a href="#">816/2025</a>                                                    |
| Beam angle [°]:                   | 120           | Manual:                                  | <a href="#">Download PDF</a>                                                |
| Diffuser type:                    | szkło         | ISO Certificates:                        | 9001:2015, 14001:2015, 45001:2018, 50001:2018                               |
| Diffuser colour:                  | transparent   | Plik LDT:                                | <a href="#">Download</a>                                                    |
| Optics material:                  | PC            |                                          |                                                                             |

Card creation date:14 August 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 106/2026



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)