

# QUEST LED EVO S ENDURA 16950LM DALI I CL. IP67 740 ASN 104W

DETAILED CARD



## TECHNICAL PARAMETERS

|                               |           |
|-------------------------------|-----------|
| Index:                        | 107658    |
| Ingress protection:           | IP67      |
| Impact resistance:            | IK10      |
| Luminous flux [lm]*:          | 16950     |
| Colour temperature [K]:       | 4000      |
| Color rendering index (Ra) >: | 70        |
| Electrical protection class:  | I         |
| Energy efficiency class:      | B         |
| Material of the body:         | aluminium |
| Colour of the body:           | RAL7016   |

## CHARACTERISTICS

The Quest LED Evo S (in the ENDURA version – resistant to elevated ambient temperatures of up to 50°C) is a member of a well-established family of floodlights, positioned in terms of size between the XS and M versions. It responds to market needs by filling a gap in the extremely popular segment of floodlights with a power output of approximately 100 W. Together with dedicated variants of industrial floodlights, the QUEST EVO forms a versatile range of premium-class luminaires, manufactured in Poland. The die-cast aluminium body is powder-coated. The design, which lacks external heat sink fins, prevents the build-up of dirt and makes maintenance much easier. The luminaire is designed for use in the most demanding environments (marine corrosion class C5-M as standard). It features the highest IP67 protection rating and the highest impact resistance rating of IK10. High-efficiency LEDs covered by tempered glass ensure a luminous efficacy exceeding 170 lm/W. A wide range of optical systems (including asymmetrical optics) guarantees a perfect match for the light distribution. Compliance with the PN-EN 60598-2 Part 5 standard classifies the luminaire as an architectural spotlight, allowing it to be fitted in any position, rotated through a full 360° and offering high resistance to gusts of wind. The use of a sealed quick-connect coupler with intuitive, colour-coded latches reduces connection time and eliminates time-consuming traditional methods. The accessory kit includes pole-mounting brackets, a frame for recessed mounting (e.g. in canopies), light pollution control screens, and protective grilles in two colours with different levels of light reduction (white RAL7016: 4%, in the body colour RAL7016: 8%). The models can be fitted with an external motion and twilight sensor.

## APPLICATION

The Quest LED EVO S ENDURA is widely used for lighting facilities with elevated temperature requirements, including educational, childcare and administrative premises, halls, garages, passageways, warehouses, shops, as well as in the food industry and retail and service premises dealing with foodstuffs. They are the ideal solution for small sports pitches, open spaces and car parks. They can be installed as floodlights on poles and masts, on building façades, as well as surface-mounted high-bay luminaires (HB NT version) and suspended high-bay luminaires (HB Z version). Thanks to the recessed mounting option, they are ideal for use in carports. The Quest LED EVO S ENDURA is an excellent choice for factories, production halls and large-scale warehouses.

# QUEST LED EVO S ENDURA 16950LM DALI I CL. IP67 740

## ASN 104W

DETAILED CARD

### TECHNICAL PARAMETERS TABLE


|                                   |               |                                          |                                                                             |
|-----------------------------------|---------------|------------------------------------------|-----------------------------------------------------------------------------|
| Index:                            | 107658        | Colour of the body:                      | RAL7016                                                                     |
| EAN:                              | 5905963107658 | Impact resistance:                       | IK10                                                                        |
| Light source:                     | LED module    | Ingress protection:                      | IP67                                                                        |
| Rated power of the luminaire [W]: | 104           | DIMM DALI:                               | yes                                                                         |
| Supply voltage [V]:               | 176-277       | Category type:                           | floodlights                                                                 |
| Frequency [Hz]:                   | 50-60         | AC voltage range [V]:                    | 90-305                                                                      |
| Luminous flux [lm]:               | 16950         | DC voltage range [V]:                    | #ADR!                                                                       |
| Luminous efficacy [lm/W]:         | 163           | Light distribution type:                 | ASN                                                                         |
| Energy efficiency class:          | B             | Photobiological safety:                  | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Electrical protection class:      | I             | Warranty [years]:                        | 5                                                                           |
| Colour temperature [K]:           | 4000          | CE certificate:                          | <a href="#">108/2026</a>                                                    |
| Color rendering index (Ra) >:     | 70            | ENEC Certificate:                        | <a href="#">0487/ENEC/26</a>                                                |
| Diffuser type:                    | glass         | Environmental Product Declaration (EPD): | <a href="#">816/2025</a>                                                    |
| Diffuser colour:                  | transparent   | Manual:                                  | <a href="#">Download PDF</a>                                                |
| Optics material:                  | PC            | ISO Certificates:                        | 9001:2015, 14001:2015, 45001:2018, 50001:2018                               |
| Optics:                           | reflector     | Plik LDT:                                | <a href="#">Download</a>                                                    |
| Material of the body:             | aluminium     |                                          |                                                                             |

# QUEST LED EVO S ENDURA 16950LM DALI I CL. IP67 740 ASN 104W


DETAILED CARD

## ACCESSORIES AVAILABLE


| index  | Name                                             |
|--------|--------------------------------------------------|
| 840401 | QUEST LED EVO S/M/L pole holder 1x               |
| 840418 | QUEST LED EVO S/M/L pole holder 2x               |
| 840098 | QUEST LED EVO XS/S/M/L wall mount MAX RAL7016 1m |
| 840388 | QUEST LED EVO S/M/L RCR set 1x                   |
| 840371 | QUEST LED EVO S/M/L RCR set 2x                   |
| 111792 | QUEST LED EVO S frame, RAL 7016                  |
| 881961 | QUEST LED EVO S protective grille, RAL 9003      |
| 881954 | QUEST LED EVO S protective grille, RAL7016       |
| 111808 | QUEST LED EVO S cover RAL7016                    |




QUEST LED EVO S/M/L pole holder  
1x (840401)




QUEST LED EVO S/M/L pole holder  
2x (840418)



QUEST LED EVO XS/S/M/L wall mount  
MAX RAL7016 1m (840098)



QUEST LED EVO S/M/L RCR set  
1x (840388)



QUEST LED EVO S/M/L RCR set  
2x (840371)

Card creation date:14 August 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 108/2026