# TRIPACT LED P 2300LM PMMA II KL. IP40/ IP20 595X595 830 (24W)

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 658006 |
| **Ingress protection:** | IP40/20 |
| **Nominal power [W]:** | 24 |
| **Luminous flux [lm]*:** | 2300 |
| **Color rendering index (Ra) >:** | 80 |
| **SDCM:** | 3 |
| **Energy efficiency class:** | F |
| **Material of the body:** | ABS |
| **Diffuser material:** | PMMA |
| **Diffuser type:** | OPAL |

## CHARACTERISTICS

TRIPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

# TRIPACT LED P 2300LM PMMA II KL. IP40/ IP20 595X595 830 (24W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 658006 |
| **Light source:** | LED module |
| **Nominal power [W]:** | 24 |
| **Rated power of the luminaire [W]:** | 25 |
| **Supply voltage [V]:** | 220-240 |
| **Frequency [Hz]:** | 50 - 60 |
| **Luminous flux [lm]:** | 2300 |
| **Luminous efficacy [lm/W]:** | 92 |
| **Energy efficiency class:** | F |
| **Electrical protection class:** | II |
| **Colour temperature [K]:** | 3000 |
| **Color rendering index (Ra) >:** | 80 |
| **SDCM:** | 3 |
| **Power factor:** | 0.95 |
| **LED lifespan L70B50 [h]:** | 132000 |
| **Diffuser material:** | PMMA |
| **Diffuser type:** | OPAL |
| **Diffuser colour:** | white |
| **Material of the body:** | ABS |
| **Colour of the body:** | white |


| | |
|---|---|
| **Dimensions (H/W/T/S) [mm]:** | 595/595/93 |
| **Mounting dimensions [mm]:** | 595/595 |
| **Ingress protection:** | IP40/20 |
| **Mounting version:** | recessed |
| **Working temperature [°C]:** | from -25 to +35 |
| **Net weight [kg]:** | 1.800 |
| **EAN:** | 5905963658006 |
| **Category type:** | troffers |
| **AC voltage range [V]:** | 198 - 264 |
| **DC voltage range [V]:** | 176 - 276 |
| **LED lifespan L80B10 [h]:** | 84000 |
| **LED lifespan L90B10 [h]:** | 42000 |
| **Light distribution type:** | lambertian |
| **Photobiological safety:** | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| **Warranty [years]:** | 5 |
| **Warranty [years]:** | 5 |
| **Manual:** | Download PDF |
| **CE certificate:** | 251/2023 |
| **Plik LDT:** | Download |

# TRIPACT LED P 2300LM PMMA II KL. IP40/ IP20 595X595 830 (24W)


DETAILED CARD

## ACCESSORIES AVAILABLE

| index | Name |
|---|---|
| 658372 | Diffuser TRIPACT |
| 374845 | Frame adapter KG 635x635 WHITE |



Diffuser TRIPACT (658372)



Frame adapter KG 635x635 WHITE (374845)



The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 251/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl