


TRIPACT LED P 3750LM PMMA II KL. IP40/ IP20 595X595 830 (42W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	658020
Ingress protection:	IP40/20
Nominal power [W]:	42
Luminous flux [lm]*:	3750
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

TRIPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

TRIPACT LED P 3750LM PMMA II KL. IP40/ IP20 595X595 830 (42W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	658020	Dimensions (H/W/T/S) [mm]:	595/595/93
Light source:	LED module	Mounting dimensions [mm]:	595/595
Nominal power [W]:	42	Ingress protection:	IP40/20
Rated power of the luminaire [W]:	43	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -25 to +35
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.800
Luminous flux [lm]:	3750	EAN:	5905963658020
Luminous efficacy [lm/W]:	87	Category type:	troffers
Energy efficiency class:	F	AC voltage range [V]:	198 - 264
Electrical protection class:	II	DC voltage range [V]:	176 - 276
Colour temperature [K]:	3000	LED lifespan L80B10 [h]:	84000
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	42000
SDCM:	3	Light distribution type:	lambertian
Power factor:	0.95	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	132000	Warranty [years]:	5
Diffuser material:	PMMA	Warranty [years]:	5
Diffuser type:	OPAL	Manual:	Download PDF
Diffuser colour:	white	CE certificate:	251/2023
Material of the body:	ABS	Pliik LDT:	Download
Colour of the body:	white		

TRIPACT LED P 3750LM PMMA II KL. IP40/ IP20 595X595 830 (42W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
658372	Diffuser TRIPACT
374845	Frame adapter KG 635x635 WHITE



Diffuser TRIPACT (658372)



Frame adapter KG 635x635
WHITE (374845)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 251/2023